22-5-2005

Link redundancy based connected topologies in ad-hoc networks

G. Srivastava

University of Wollongong, gauravs@uow.edu.au

P. Boustead

University of Wollongong, boustead@uow.edu.au

Joe F. Chicharo

University of Wollongong, chicharo@uow.edu.au

Follow this and additional works at: <https://ro.uow.edu.au/infopapers>

Part of the [Physical Sciences and Mathematics Commons](#)

Recommended Citation

Srivastava, G.; Boustead, P.; and Chicharo, Joe F.: Link redundancy based connected topologies in ad-hoc networks 2005.

<https://ro.uow.edu.au/infopapers/458>

Link redundancy based connected topologies in ad-hoc networks

Abstract

The topology of a wireless network can have a significant impact on the connectivity, fault tolerance and longevity of a network. Power optimised topology control algorithms including a relative neighbourhood graph (RNG) and a minimum spanning tree (MST) reduce the links in a network topology, while keeping a topology connected. Link redundancy may be critical to cope with faults such as node failures and link disruptions. In this paper, we analyse the fault tolerance of a number of topology control algorithms. We propose a new distributed mechanism to increase the fault tolerance of power optimised topology control algorithms. The proposed mechanism can be used in the case of node failures, where extra link redundancy may be crucial to provide a connected topology. We compare the connectivity, fault tolerance, transmission power and the hop diameter of the proposed approach against RNG, MST and the 'minimum node degree' graphs for different node degree values. Simulations indicates that the proposed approach provides a distributed mechanism to enhance the fault tolerance and connectivity of RNG and MST topology graphs for high node failure rates.

Disciplines

Physical Sciences and Mathematics

Publication Details

This article was originally published as: Srivastava, G, Boustead, P & Chicharo, J, Link redundancy based connected topologies in ad-hoc networks, IEEE International Conference on Electro Information Technology 2005, 22-25 May 2005. Copyright 2005 IEEE.

Link Redundancy Based Connected Topologies in Ad-hoc Networks

Gaurav Srivastava, Paul Boustead, Joe Chicharo
School of Electrical, Computer and Telecommunication Engineering,
University of Wollongong, NSW, Australia.
Email: gaurav@titr.uow.edu.au, paul@titr.uow.edu.au, chicharo@uow.edu.au

Abstract—The topology of a wireless network can have a significant impact on the connectivity, fault tolerance and longevity of a network. Power optimised topology control algorithms including a Relative Neighbourhood Graph (RNG) and a Minimum Spanning Tree (MST) reduce the links in a network topology, while keeping a topology connected. Link redundancy may be critical to cope with faults such as node failures and link disruptions. In this paper, we analyse the fault tolerance of a number of topology control algorithms. We propose a new distributed mechanism to increase the fault tolerance of power optimised topology control algorithms. The proposed mechanism can be used in the case of node failures, where extra link redundancy may be crucial to provide a connected topology. We compare the connectivity, fault tolerance, transmission power and the hop diameter of the proposed approach against RNG, MST and the ‘minimum node degree’ graphs for different node degree values. Simulations indicate that the proposed approach provides a distributed mechanism to enhance the fault tolerance and connectivity of RNG and MST topology graphs for high node failure rates.

I. INTRODUCTION

An ad-hoc network is a group of autonomous wireless nodes working together to form a network. Nodes in an ad-hoc network can be battery powered devices with limited transmission capabilities. Power conservation can be a critical factor to enhance the lifetime of a network.

The topology of a wireless network can have a significant impact on the available network resources including connectivity, power usage, network lifetime, bandwidth and delay. Power optimised topology control algorithms model a network topology as a Graph (V, E) , where ‘V’ are the vertices and ‘E’ are the edges. The vertices represent the nodes in a network and edges represent the links. A Minimum Spanning Tree (MST) and a Relative Neighbourhood Graph (RNG), reduce the number of links in a topology graph, while maintaining a connected topology. The total power usage in a MST or a RNG can be reduced by adjusting the transmission power to cover the link distance between two nodes, and using the minimum power routes to forward the data packets [1]. There are various applications of MST and RNG graphs in power optimised routing and flooding [2].

The signal attenuation characteristics, node mobility and low battery power can make wireless links unreliable and result in frequent link disruptions and node failures. In the presence of node failures, a low link redundancy solution including a MST and a RNG may result in a disconnected

network and introduce unnecessary delay in network communications.

A ‘minimum node degree’ graph [3] aims to maintain a minimum number of one hop neighbours by controlling the ‘node degree’ parameter. The ‘node degree’ of a node is equal to the nodes within its transmission range or the number of edges incident at a vertex in a topology graph. Numerous node degree values have been proposed to establish a highly probable connected network [4] [5] [6].

A minimum node degree graph can be more fault tolerant than a MST and a RNG [7], however a ‘minimum node degree’ graph fails to provide a fully connected network and may result in ‘isolated nodes’ and ‘disjointed clusters’ [8][9]. Furthermore, average transmission power used by a ‘minimum node degree’ graph is significantly larger than a MST and a RNG graph [7].

In this paper we propose a new distributed mechanism to select and add extra link/s to the power optimised topology graphs. The link selection is based on a ‘redundancy’ metric, which utilises two hop neighbours and their local topology graph information. A collaborative procedure proposed in [9] is used in conjunction with the neighbour discovery protocol to provide a bidirectional topology graph. The proposed algorithm is applied to the MST and RNG graphs and their connectivity, fault tolerance, transmission power and hop diameter are evaluated for increasing network size and node failure rates.

Section II of the paper provides an overview of the topology control algorithms. Section III discusses the proposed approach. Section IV illustrates the operation of the proposed approach with an aid of a worked example. Section V provides a simulation based analysis of the proposed approach. Section VI concludes the paper.

II. TOPOLOGY CONTROL ALGORITHMS

A MST of a graph defines the smallest subset of edges that keeps the graph in one connected component [10]. There are two main algorithms, (1) *Kruskal’s Algorithm* [11] and (2) *Prim’s Algorithm* [11] for computing a MST. *Kruskal’s* algorithm chooses edges of the graph with minimum weight. *Prim’s* algorithm builds the MST by putting an arbitrary node into a tree. This eliminates the search step required in the *Kruskal’s* algorithm. The edges are added to the graph if they are smaller than the previous edges already in the graph.

Fig. 1. [8](a) K-Neigh based topology graph with nd=2. (b) K-Neigh based bidirectional topology graph with nd=2. (c) Alone Soldier problem in K-Neigh based topology graph with nd=2.

The RNG of a N node network is exactly those pairs (i, j) of nodes, for which there is no node ' z ' such that $\|r_i - r_z\| < \|r_i - r_j\|$ and $\|r_j - r_z\| < \|r_j - r_i\|$ where ' r_i ' denotes the position vector of node ' i ' [12] [13] [14]. Hence an edge between ' i ' and ' j ' is only valid if there is no other node between ' i ' and ' j ' that satisfies the condition stated above.

A '*minimum node degree graph*' is a topology graph where the edges incident at a node are equal to or lower than ' x ', where ' x ' is the target 'node degree' (nd) parameter. A number of topology control algorithms have been proposed to maintain a minimum node degree. Such algorithms include K-Neigh [15], Location Information No Topology (LINT) [16], and MobileGrid (MG) [17]. A 'minimum node degree' graph may not result in a connected network and the connectivity of a network can depend on numerous parameters such as node distribution pattern, node degree value and the size of a network. In order to illustrate the disconnected nature of 'minimum node degree' graphs, Figures 1(a), 1(b) and 1(c) are analysed.

Figures 1(a) and 1(b) are the plots of a 5 node network topology with a minimum node degree requirement of 2. A line represents a link and an arrow represents the direction of a link. When executing K-Neigh [15], the local unidirectional topology graphs of nodes 0, 4 and 3 comprises of links $\{r_{04}, r_{03}\}$, $\{r_{04}, r_{43}\}$, and $\{r_{35}, r_{32}\}$ respectively. After exchanging the local unidirectional topology graphs, the bidirectional links of nodes 0, 4 and 3 are $\{r_{04}\}$, $\{r_{04}\}$, and $\{r_{35}, r_{32}\}$ respectively. The bidirectional topology in Figure 1(b) is disconnected, since links ' r_{03} ' and ' r_{43} ' are unidirectional and are not included.

The fixed node degree approach may also create an 'alone soldier' problem [3], illustrated in Figure 1(c). This occurs when nodes 3, 4 and 6 have met their local node degree requirements and their local topology graphs do not contain a link to node 0, where as node 0 may have added unidirectional links to these nodes. There can be many topology distributions where the local node degree requirements may be met, but the bidirectional node degree requirements may not be satisfied. As the result of this, the bidirectional node degree graphs may be disconnected [8].

In [7] the connectivity, power usage and the hop diameter of

'minimum node degree' graphs is analysed for a range of node degree values and node failure rates. It was observed that in the case of node failures, a 'minimum node degree' graph has a better chance of maintaining a connected network as compared to a MST and a RNG [7]. However, the transmission power of 'minimum node degree' graphs is significantly larger than MST and RNG topology graphs [7].

III. PROPOSED ALGORITHM

The aim of the proposed algorithm, Link Redundancy (LR), is to add extra link/s to a power optimised topology in order to enhance it's fault tolerance. The links are added on the basis of their 'redundancy' value, which is calculated in a distributed manner by examining the one hop connectivity of a probable redundant link and comparing it with the 1^{st} and 2^{nd} hop connectivity of a node executing the LR algorithm. This allows a node to evaluate a redundancy parameter for each link which was not initially included in the topology graph. A high redundancy value implies a larger chance of providing connectivity with the 1^{st} and 2^{nd} hop topology control neighbours. This is different to the 'minimum node degree' graphs, where links are added on the basis of their distance from the reference node.

A topology graph is generated locally when executing a distributed topology control algorithm, including Distributed Relative Neighbourhood Graph (DRNG), Localised Minimum Spanning Tree (LMST) and K-Neigh or can be constructed and disseminated by a central node in the case of centralised algorithms, including RNG and MST.

The neighbour information is evaluated by exchanging "Hello" messages at the maximum power [18]. A "Hello" message contains the identification (ID) of the broadcasting node and is used to evaluate a list of unidirectional neighbouring nodes (N_i). The ID is a unique number assigned to a node to maintain its identity in a network, for example Internet Protocol (IP) address. A node's ID is used to construct a Topology Control Neighbour (TCN) list comprising of the nodes in the topology graph. A TCN list is generated by executing a particular topology control algorithm and is a subset of the maximum power neighbours (N_i).

Bidirectional TCNs are evaluated by appending the TCN list to a "Hello" packet and broadcasting it at the maximum power. Nodes receiving the broadcast are able to determine the bi-directional TCNs (BTCNs) by using the *Bidirectional-TCN()* function, where BTCNs are evaluated by performing a search between local TCNs and the one hop neighbouring TCNs.

The unique two hop TCNs of node ' i ' are depicted by set ' E_i ' and is evaluated by calculating the set of nodes which are unique 1^{st} and 2^{nd} hop TCN neighbours of node ' i '. The two hop TCN list of node ' i ' ($TCN_i \cup TCN(TCN_i)$), includes nodes which are TCNs of nodes ' i ' and conjointly the set of nodes which are the TCNs of every TCN of node ' i ', as shown in Equation 1.

$$E_i = TCN_i \cup TCN(TCN_i) \neq i, \notin E_i \quad (1)$$

Each node calculates a set of possible links which are **not** in its local topology graph but are within its transmission range. This set is represented by set ' T_i ' and is evaluated by removing the TCNs of node ' i ' from ' N_i ' ($T_i = \{N_i - TCN_i\}$). A *Construct-LR()* function is proposed, where each node initially calculates sets ' E_i ' and ' T_i ', and then calculated the **redundancy** (R_j) of each node $j \in T_i$. ' R_j ' is calculated by evaluating the total number of nodes in set ' TCN_j ' which are common to set E_i and dividing the total by the total number of nodes in E_i as depicted in Equation 2.

$$R_j = \frac{\sum TCN_j \cap E_i \cap j}{\sum E_i}, i \neq j, j \in T_i \quad (2)$$

In order to add an extra redundant link, node ' i ' executes the *Add-LR()* function and adds node ' $j \in T_i$ ' which has the maximum redundancy value ' R_j ', to the topology graph of node ' i '. In case of a deadlock where links may have equal redundancy values, link ' r_{ij} ' with the least distance to node ' i ' is chosen in order to conform with the power saving objectives of a power aware topology control algorithm.

Unidirectional TCNs are converted to BTCNs by using the *Convert-TCN()* function, which uses a search to evaluate the unidirectional TCNs and add a corresponding link. A node iterates through its neighbour's TCN list and adds the neighbour's ID to its local TCN list, if there is a unidirectional link from its neighbour to itself. The conversion of unidirectional TCNs to bidirectional TCNs does not require any message exchange apart from the "Hello" messages. We assume that all nodes are *Collaborative* and are willing to support such decisions. This procedure is critical as unidirectional links cannot be used for unicast communication and do not improve the bidirectional connectivity of a network.

Algorithm Bidirectional-TCN()

(* Find Bidirectional TCN list *)

1. $TCN_i \leftarrow$ Local uni-directional TCN list of node i
2. $BTCN_i \leftarrow$ Local bi-directional TCN list of node i
3. **if** $TCN_i \neq 0$
4. **for** each node k in TCN_i
5. $j \leftarrow$ Calculate node k 's TCNs
6. **while** $j \neq 0$
7. **if** $j = i$
8. **then** Add k to $BTCN_i$
9. **return** $BTCN_i$

Algorithm Construct-LR()

(* Construct a R_j list *)

1. $N_i \leftarrow$ 1-hop unidirectional neighbours of node i , sorted in the order of their distance from i
2. $BTCN_i \leftarrow$ Local bi-directional TCNs of node i
3. $T_i \leftarrow$ Set of nodes $\in \{N_i - BTCN_i\}$
4. $E_i \leftarrow BTCN_i \cup BTCN(BTCN_i) \neq i, \notin E_i$
5. $E_{i_count} \leftarrow$ Total number of nodes in E_i
6. $R_j \leftarrow$ Redundancy value of node j
7. $count \leftarrow$ Count of the common elements
8. **for** each node $j \in T_i$
9. $BTCN_j \leftarrow$ Calculate node j 's BTCN

(a) A RNG based network topology

(b) A LR-RNG based network topology

Fig. 2.

10. **for** each node $l \in BTCN_j$
11. **if** ($l \in E_i$ or $j \in E_i$)
12. $count = count + 1$
13. $R_j = count / E_{i_count}$
14. $count = 0$
15. **return** R

Algorithm Add-LR()

(* Add a redundant link to the topology graph *)

1. $N_i \leftarrow$ 1-hop unidirectional neighbours of node i , sorted in the order of their distance from i
2. $TCN_i \leftarrow$ Local uni-directional TCNs of node i
3. $BTCN_i \leftarrow$ Local bi-directional TCNs of node i
4. $R_j \leftarrow$ Redundancy value of node j
5. $T_i \leftarrow$ Set of nodes $\in \{N_i - BTCN_i\}$
6. $R_{max} \leftarrow$ maximum redundancy value
7. $R_{index} \leftarrow$ maximum redundancy index
8. $r_{ij} \leftarrow$ Distance between node ' i ' and ' j '.
9. $R_{max} = 0$
10. **for** each node $j \in T_i$
11. **if** ($R_j > R_{max}$)
12. $R_{max} = R_j$
13. $R_{index} = j$
14. **if** ($R_j == R_{max}$ and $R_{max} \neq 0$)
15. **if** ($r_{ij} < r_{iT(R_{index})}$)
16. $R_{index} = j$
17. Add $T(R_{index})$ to TCN_i
18. **return** TCN_i

Algorithm Convert-TCN()

(* Convert unidirectional to bidirectional TCN *)

1. $N_i \leftarrow$ 1-hop unidirectional neighbours of node i
2. $BTCN_i \leftarrow$ Local bi-directional TCN list of node i
3. **if** $N_i \neq 0$
4. **for** each node k in N_i
5. $j \leftarrow$ TCN of node k
6. **if** $i = j$ and $k \notin BTCN_i$
7. **then** Add k to $BTCN_i$
8. **return** $BTCN_i$

IV. WORKED EXAMPLE

Figure 2(a) is a RNG topology graph of a 10 node network. Figure 2(b) is a topology graph of LR applied to the RNG topology (LR-RNG) depicted in Figure 2(a). In Figure 2(b), a number of redundant links are included which were not preset in Figure 2(a). Example of such links include $\{1 \rightarrow 7\}$, $\{4 \rightarrow 8\}$, $\{5 \rightarrow 6\}$, $\{6 \rightarrow 5\}$, $\{8 \rightarrow 4\}$ and $\{7 \rightarrow 1\}$. The details of the LR-RNG calculation are as follows:-

Node 1: (i=1)

$$TCN_1 = \{3, 8\}$$

$$E_1 = \{3, 8, 0, 7\}, \text{ using equation 1}$$

$$T_1 = \{4, 7\}, \text{ two redundant links to check.}$$

Checking node 4: (j=4)

$$TCN_4 = \{7\}$$

$$TCN_4 \cap E_1 \cap 4 = \{1\}$$

$$R_4 = \frac{1}{4} = 0.25, \text{ using equation 2}$$

Checking node 7: (j=7)

$$TCN_7 = \{4, 8\}$$

$$TCN_7 \cap E_1 \cap 7 = \{8, 7\}$$

$$R_7 = \frac{2}{4} = 0.50, \text{ using equation 2}$$

Since $R_7 > R_4$, node 7 is added to the topology graph of node 1, and hence $TCN_1 = \{3, 7, 8\}$

Node 4: (i=4)

$$TCN_4 = \{7\}$$

$$E_4 = \{7, 8\}, \text{ using equation 1}$$

$$T_4 = \{1, 8\}, \text{ two redundant links to check.}$$

Checking node 1: (j=1)

$$TCN_1 = \{3, 7, 8\} \text{ Note that } TCN_1 \text{ now includes node 7}$$

$$TCN_1 \cap E_4 \cap 1 = \{7, 8\}$$

$$R_1 = \frac{2}{2} = 1.00, \text{ using equation 2}$$

Checking node 8: (j=8)

$$TCN_8 = \{1, 7\}$$

$$TCN_8 \cap E_1 \cap 8 = \{7, 8\}$$

$$R_8 = \frac{2}{2} = 1.00, \text{ using equation 2}$$

Since $R_8 = R_1$, node 8 is added to the topology graph of node 4, as the distance of node 4 to node 1 is greater than distance of node 4 to node 8 ($r_{41} > r_{48}$). Hence $TCN_4 = \{7, 8\}$

Node 5: (i=5)

$$TCN_5 = \{2, 9\}$$

$$E_5 = \{2, 9, 0, 6\}, \text{ using equation 1}$$

$$T_5 = \{6\}, \text{ one redundant links to check.}$$

Checking node 6: (j=6)

$$TCN_6 = \{9\}$$

$$TCN_6 \cap E_5 \cap 6 = \{6, 9\}$$

$$R_6 = \frac{2}{4} = 0.50, \text{ using equation 2}$$

Since R_6 is the only node to check, node 6 is added to the topology graph of node 5. A preprocessing phase can be introduced here to avoid the redundancy calculation if there is only one T node to check. Hence $TCN_5 = \{2, 6, 9\}$. Similarly nodes 6, 7 and 8 have only one node in their T set ($T_6 = \{5\}, T_7 = \{1\}, T_8 = \{4\}$), and have added corresponding links to those nodes.

The topology in Figure 2(b) is more fault tolerant than Figure 2(a). For example, in case of the failure of nodes 7 and 9 the topology graph of LR-RNG will still be connected, where as in the case of RNG, nodes 6 and 4 will be be disconnected from the network. In the case of higher network densities, there can be many nodes in the 'T' and 'E' sets of a node, and worked examples can become complicated. The following section provides the simulation based analysis of the LR algorithm for increasing network size.

V. SIMULATION

A simulation of the topology graphs has been conducted to examine the performance of LR-MST, LR-RNG, Maximum Power Topology (MPT), RNG, MST and K-Neigh (nd=1,2,3,4,5,6,7,8) algorithms in a static network. In this study, the LR algorithm is executed locally to choose **one** additional redundant link per node. The nodes are distributed in a random manner in a 600m X 600m grid area and varied in number from 10 to 100. All nodes have a maximum transmission range of 200m. The simulation results are averaged over 500 random seeds. In order to model node failures due to an 'expired battery' or nodes being 'switched off', faults are introduced in a network by randomly removing a set of nodes from a topology graph.

The performance metrics studied are as follows:- (1) The **Average network connectivity**, is defined as the average of the 'mean connectivity'. The 'mean connectivity' of node 'i' is given by $c_i = \frac{x}{N}$, where 'x' is the number of nodes reachable by node 'i' and 'N' is the total number of nodes in a network. The average network connectivity of the entire network is evaluated by averaging the mean connectivity at every node and is given by $\frac{1}{N} \sum_{i=0}^{N-1} c_i$. (2) The **Average transmission power**, is defined as the average of the 'mean transmission power' per link, at each node. The 'mean transmission power' of node 'i' is given by $p_i = \frac{\sum_{j=1}^L p_{ij}}{L}$, where p_{ij} is the power required to reach link (i,j) and 'L' are the total number of links in local topology graph of node 'i'. The average transmission power of the entire network is evaluated by averaging the mean transmission power per link at every node and is given by $\frac{1}{N} \sum_{i=0}^{N-1} p_i$. (3) The **Average hop diameter**, is the mean of the maximum number of hops reachable by a node. (4) The **Average one hop neighbours**, are the mean one hop bidirectional neighbours in the topology graph.

A. Results

A study of the average network connectivity of the RNG, MST, MPT and LINT (nd=1,2,3,4,5,6) topology graphs has been conducted in [7]. Figure 3 is the plot of the average network connectivity against the number of network nodes. MPT, MST, RNG and LINT (nd=6,7,8) are able to reach $\approx 100\%$ connectivity at ≈ 40 nodes [7]. The node degree values of 1, 2 and 3 show significantly lower connectivity than other node degree values examined. Since the node degree values of 1, 2, 3 and 4 illustrate connectivity below 95%, only node degree values of 5, 6, 7 and 8 are studied ahead.

Fig. 3. [7] A comparison of the average network connectivity of the topology control algorithms.

Fig. 4. A comparison of the fault tolerance of the topology control algorithms.

Figure 4 is a plot of the average network connectivity for a 100 node network, against the node failure rate. LR-RNG, RNG, MST, LR-MST, MPT and K-Neigh (nd=5,6,7,8) illustrate a decrease in network connectivity with an increase in the failure rate. As expected, MST provides a least fault tolerant topology, and MPT provides the most fault-tolerant topology.

The average network connectivity of MST at 5% failure rate is $\approx 44\%$, whereas the connectivity of LR-MST, LR-RNG, MPT, RNG and K-Neigh (nd=5,6,7,8) are $\approx 71\%$ and $\approx 90\%$, $\approx 90\%$, $\approx 87\%$, $\approx \{88, 89, 90, 3, 90, 4\}\%$ respectively. LR-MST illustrates a significant improvement in the connectivity of MST at the 5% node failure rate.

In the case of 15% node failure rate, the connectivity of LR-RNG and K-Neigh(nd=6) are $\approx 70\%$, whereas the connectivity of RNG is $\approx 53\%$. The connectivity of LR-MST and MST are $\approx 34\%$ and $\approx 15\%$.

In the case of a 30% node failure rate, the connectivity of LR-MST, LR-RNG, MPT, MST, RNG and K-Neigh (nd=5,6,7,8) are $\approx 14\%$, $\approx 38\%$, $\approx 54.6\%$, $\approx 7\%$, $\approx 22\%$ and $\approx \{40, 44, 52.7, 53.7\}\%$ respectively. The connectivity of LR-MST, and LR-RNG are ≈ 2 and ≈ 1.7 times larger than MST and RNG respectively. The connectivity of LR-RNG is $\approx 6\%$ lower than K-Neigh(nd=6) and $\approx 16\%$ lower than MPT in the case of 30% node failure rate.

Fig. 5. A comparison of the average one hop bi-directional neighbours of the topology control algorithms.

Fig. 6. A comparison of the average transmission power of the topology control algorithms.

In general the connectivity of MST and RNG is significantly improved by applying the LR algorithm. The connectivity of LR-RNG is now comparable to the connectivity of K-Neigh(nd=6) until the node failure rate of $\approx 20\%$ and is only $\approx 3\%$ lower than MPT.

Figure 5 is a plot of the average one hop bidirectional neighbours against the total number of network nodes. As expected MPT graph illustrates the maximum number of one hop neighbours where as a MST graphs shows the minimum number of one hop neighbours. In a 100 node network, the average one hop neighbours of RNG and MST are ≈ 2.4 and ≈ 2 respectively, whereas of LR-RNG and LR-MST are ≈ 4.1 and ≈ 3.7 respectively. As expected the number of one hop neighbours in LR-RNG and LR-MST are larger than RNG and MST topology graphs. The number of neighbours in the case of LR-RNG are $\approx 50\%$ less than than one hop neighbours in the case of K-Neigh(nd=6).

Figure 6 is a plot of the average transmission power against the total number of network nodes. The average transmission power of MPT remains constant at ≈ 1.1 dBm/link. The average transmission power in the case of LR-MST, LR-RNG, RNG, MST and K-Neigh decreases with an increase in the number of nodes. In a 100 node network the average transmission power of LR-MST, LR-RNG, MST, RNG and

Fig. 7. A comparison of the hop diameter of the topology control algorithms.

K-Neigh (nd=5,6,7,8) are ≈ -6.6 dBm, ≈ -5.9 dBm, ≈ -8.8 dBm, ≈ -7.6 dBm and $\approx \{0.86, -4.9, 1.16, 1.54\}$ dBm respectively. The average transmission power of LR-RNG is $\approx 22\%$ larger than RNG, and the power of LR-MST is $\approx 25\%$ larger than MST. The power increase is due to the extra links added by executing the LR algorithm. However, the powers used by LR-MST and LR-RNG are $\approx 35\%$, $\approx 20\%$ lower than K-Neigh (nd=6) and are significantly lower than MPT.

Figure 7 is a plot of the average hop diameter against the number of network nodes. The hop diameter increases with an increase in the number of nodes. MPT has the smallest hop diameter, whereas MST has the largest hop diameter. The hop diameters of LR-MST, LR-RNG, MST, RNG, MPT and K-Neigh (nd=5,6,7,8), for a 100 node network are ≈ 20.6 , ≈ 11.5 , ≈ 32 , ≈ 16 , ≈ 3.8 and $\approx \{11.02, 10.6, 8.3, 6.02\}$ respectively. In a 100 node network the hop diameters of RNG and K-Neigh (nd=5,6,7,8) are $\approx 50\%$ and $\approx \{62 - 79\}\%$ lower than MST respectively. As expected the hop diameter of LR-MST and LR-RNG are lower than the hop diameters of MST and RNG respectively. The decrease in the hop diameter is due to the larger transmission power used in the LR based topology graphs.

In summary, the LR algorithm illustrates significant improvement in the connectivity of MST and RNG in the case of node failures. The connectivity of LR-RNG is comparable to the connectivity of K-Neigh and MPT until the node failure rate of 20%, as opposed to node failure rate of 5% observed in the case of RNG. The power usage of the LR-RNG algorithm is lower than the K-Neigh graph, and significantly lower than the MPT graph. Furthermore, K-Neigh cannot guarantee a connected network and the overall network connectivity value is dependant on various parameters such as the target 'node degree', maximum transmission range of the nodes and the network density [7]. The average one hop neighbours in the case of LR-RNG and LR-MST are lower than K-Neigh and significantly lower than MPT.

VI. CONCLUSION

In this paper we have proposed a new distributed approach (LR) to calculate the redundancy of links in a topology graph.

We have applied the proposed algorithm to MST and RNG and have compared it with the topology graphs of MST, RNG and K-Neigh. A simulation based study has been conducted to examine the effects of network faults on the performance of the LR algorithm.

REFERENCES

- [1] Ivan Stojmenovic and Xu Lin, "Power-aware localised routing in wireless networks," in *IEEE Transactions on Parallel and Distributed Systems*, Vol. 12, No. 10, Oct. 2001.
- [2] Lipman J., Boustead P., Chicharo J., and Judge J., "Optimised flooding in ad hoc networks," in *In proceedings of The 2nd Workshop on the Internet, Telecommunications and Signal Processing (WITSP'03)*, Coolangatta, Gold Coast, Australia, Dec. 2003.
- [3] Christian Bettstetter, "On the minimum node degree and connectivity of a wireless multihop network," in *Proceedings of the 3rd ACM international symposium on Mobile ad hoc networking & computing*, 2002.
- [4] L. Klienrock and J. Silvester, "Optimum transmission radii for packet radio networks or why six is a magic number," in *Proceedings of the IEEE National Telecommunication Conference*, 1978, pp. 4.3.1-4.3.5.
- [5] Feng Xue and P.R. Kumar, "The number of neighbours needed for connectivity of wireless networks," in *To appear in Wireless Networks*.
- [6] E.M. Royer, P.M. Melliar-Smith, and L.E. Moser, "An analysis of the optimum node density for ad hoc mobile networks," in *Proceedings of the IEEE International Conference on Communications*, 2001.
- [7] G. Srivastava, P. Boustead, and J. Chicharo, "Fault tolerant topologies in ad-hoc networks," in *Proceeding of Australian Telecommunications, Networks and Applications Conference, ATNAC*, 2004.
- [8] G. Srivastava, P. Boustead, and J. Chicharo, "Achieving a minimum node degree in ad-hoc networks," in *In proceedings of The 3rd Workshop on the Internet, Telecommunications and Signal Processing (WITSP'04)*, Adelaide, Australia. IEEE, Dec. 2004.
- [9] G. Srivastava, P. Boustead, J. Chicharo, and C. Ware, "Topology control in heterogeneous ad-hoc networks," in *Proceedings of the 12th IEEE International Conference on Networks (ICON 2004)*, December 2004.
- [10] Ning Li, Jennifer C. Hou, and Lui Sha, "Design and analysis of an mst-based topology control algorithm," in *The 22nd Annual Joint Conference of the IEEE Computer and Communications Societies INFOCOM*, 2003.
- [11] Nicos Christofides, *Graph Theory: An Algorithmic Approach*, Academic press, 1975.
- [12] Chi-Fu Huang, Yu-Chee Tseng, Shih-Lin Wu, and Jang-Ping Sheu, "Distributed topology control algorithm for multihop wireless networks," in *Proceedings of the International Joint Conference on Neural Networks*, 2002, pp. 355-360.
- [13] Kenneth J. Supowit, "The relative neighbourhood graph with application to minimum spanning trees," in *Journal of the ACM*, vol. 30, no. 3, pp 428-448, 1983.
- [14] Jerzy W. Jaromczyk and Godfried T. Toussaint, "The relative neighbourhood graphs and their relatives," in *Proceedings of the IEEE*, Vol. 80, No 9, Sept. 1992.
- [15] Douglas M. Blough, Mauro Leoncini, Giovanni Resta, and Paolo Santi, "The k-neigh protocol for symmetric topology control in ad hoc networks," in *Proceedings of the 4th ACM international symposium on Mobile ad hoc networking & computing*, 2003.
- [16] R. Ramanathan and R. Rosales-Hain, "Topology control of multihop wireless networks using transmit power adjustment," in *Proceedings of IEEE INFOCOM*, 2000.
- [17] Jilei Liu and Baochun Li, "Mobilegrid: Capacity-aware topology control in mobile ad hoc networks," in *Proceedings of the Eleventh International Conference on Computer Communications and Networks, ICCCN*, 2002, pp. 570-574.
- [18] C.E Perkins and E.M. Bending-Royer, "Ad hoc On-Demand Distance Vector Routing Protocol for Mobile Ad Hoc Networks," in *draft-ietf-manet-aodv-11.txt*, June 2002.