University of Wollongong

Research Online

Faculty of Science, Medicine and Health -
Papers: Part B

Faculty of Science, Medicine and Health

1-1-2020

Determining Bathymetry of Shallow and Ephemeral Desert Lakes Using Satellite Imagery and Altimetry

M Armon

E Dente

Y Shmilovitz

A Mushkin

Tim J. Cohen

University of Wollongong, tcohen@uow.edu.au

See next page for additional authors

Follow this and additional works at: <https://ro.uow.edu.au/smhpapers1>

Publication Details Citation

Armon, M., Dente, E., Shmilovitz, Y., Mushkin, A., Cohen, T. J., Morin, E., & Enzel, Y. (2020). Determining Bathymetry of Shallow and Ephemeral Desert Lakes Using Satellite Imagery and Altimetry. Faculty of Science, Medicine and Health - Papers: Part B. Retrieved from <https://ro.uow.edu.au/smhpapers1/1293>

Research Online is the open access institutional repository for the University of Wollongong. For further information contact the UOW Library: research-pubs@uow.edu.au

Determining Bathymetry of Shallow and Ephemeral Desert Lakes Using Satellite Imagery and Altimetry

Abstract

©2020. American Geophysical Union. All Rights Reserved. Water volume estimates of shallow desert lakes are the basis for water balance calculations, important both for water resource management and paleohydrology/climatology. Water volumes are typically inferred from bathymetry mapping; however, being shallow, ephemeral, and remote, bathymetric surveys are scarce in such lakes. We propose a new, remote-sensing-based, method to derive the bathymetry of such lakes using the relation between water occurrence, during >30 year of optical satellite data, and accurate elevation measurements from the new Ice, Cloud, and Land Elevation Satellite-2 (ICESat-2). We demonstrate our method at three locations where we map bathymetries with ~0.3 m error. This method complements other remotely sensed, bathymetry-mapping methods as it can be applied to: (a) complex lake systems with subbasins, (b) remote lakes with no in-situ records, and (c) flooded lakes. The proposed method can be easily implemented in other shallow lakes as it builds on publically accessible global data sets.

Publication Details

Armon, M., Dente, E., Shmilovitz, Y., Mushkin, A., Cohen, T., Morin, E. & Enzel, Y. (2020). Determining Bathymetry of Shallow and Ephemeral Desert Lakes Using Satellite Imagery and Altimetry. *Geophysical Research Letters*, 47 (7),

Authors

M Armon, E Dente, Y Shmilovitz, A Mushkin, Tim J. Cohen, E Morin, and Y Enzel

Geophysical Research Letters

RESEARCH LETTER

10.1029/2020GL087367

Special Section:

The Ice, Cloud and land Elevation Satellite-2 (ICESat-2) on-orbit performance, data discoveries and early science

Key Points:

- A new methodology to produce bathymetry maps of shallow desert lakes was developed, based on globally available data sets
- The methodology enables mapping the bathymetry of lakes with subbasins or partially flooded lakes, both major limitations of other methods
- The derived bathymetry error is ~30 cm, rather than ~2.5 m for other globally available data

Supporting Information:

- Supporting Information S1

Correspondence to:

M. Armon,
moshe.armon@mail.huji.ac.il

Citation:

Armon, M., Dente, E., Shmilovitz, Y., Mushkin, A., Cohen, T. J., Morin, E., & Enzel, Y. (2020). Determining bathymetry of shallow and ephemeral desert lakes using satellite imagery and altimetry. *Geophysical Research Letters*, 47, e2020GL087367. <https://doi.org/10.1029/2020GL087367>

Received 3 FEB 2020

Accepted 22 MAR 2020

Accepted article online 28 MAR 2020

Determining Bathymetry of Shallow and Ephemeral Desert Lakes Using Satellite Imagery and Altimetry

M. Armon¹ , E. Dente^{1,2,3} , Y. Shmilovitz^{1,2} , A. Mushkin², T. J. Cohen⁴, E. Morin¹ , and Y. Enzel¹

¹The Fredy and Nadine Herrmann Institute of Earth Sciences, the Hebrew University of Jerusalem, Jerusalem, Israel, ²The Geological Survey of Israel, Jerusalem, Israel, ³Shamir Research Institute, University of Haifa, Haifa, Israel, ⁴School of Earth and Environmental Sciences, University of Wollongong, Wollongong, New South Wales, Australia

Abstract Water volume estimates of shallow desert lakes are the basis for water balance calculations, important both for water resource management and paleohydrology/climatology. Water volumes are typically inferred from bathymetry mapping; however, being shallow, ephemeral, and remote, bathymetric surveys are scarce in such lakes. We propose a new, remote-sensing-based, method to derive the bathymetry of such lakes using the relation between water occurrence, during >30 year of optical satellite data, and accurate elevation measurements from the new Ice, Cloud, and Land Elevation Satellite-2 (ICESat-2). We demonstrate our method at three locations where we map bathymetries with ~0.3 m error. This method complements other remotely sensed, bathymetry-mapping methods as it can be applied to: (a) complex lake systems with subbasins, (b) remote lakes with no in-situ records, and (c) flooded lakes. The proposed method can be easily implemented in other shallow lakes as it builds on publically accessible global data sets.

Plain Language Summary Lakes in desert environments are often remote and shallow and only get filled once in a long while. They are an important water resource and could be used to decipher past environmental conditions. However, detailed maps of lake-floor terrain, which are required to effectively study these lakes are typically not available. The deepest parts of the lakes are filled with water more frequently than their shallow margins. Thus, we suggest here to relate water occurrence in those lakes with accurate satellite-based elevation measurements, to obtain a valuable lake-floor terrain map. We demonstrate the usefulness of our method by comparing results with other globally available data. Previous methods struggle with complex-terrain lakes or lakes that are partially flooded during their survey, while our method yields high-resolution accurate maps even in such lakes.

1. Introduction

A major characteristic of drylands is endoreism, internal drainage (de Martonne, 1927). The lower and usually drier parts of these drylands are often occupied by ephemeral or seasonal shallow desert lakes (Nicholson, 2011). Thousands of such lakes exist globally with the largest being Lake Eyre (Australia, alias Kati Thanda; surface area of >9,000 km² when full). Such lakes are significant for opportunistic species that have no other water resources (e.g., D'Odorico & Porporato, 2006; Noy-Meir, 1973). Mapping of lake floors is key in calculating water balance (e.g., Cohen et al., 2015; Enzel & Wells, 1997), important in water resources management, and in deciphering paleohydrology (e.g., Crétaux et al., 2016; Quade et al., 2018). However, being shallow, dry, and remote, bathymetric surveys (e.g., as in Bye et al., 1978) have been scarce in such lakes.

A different approach to bathymetry mapping is through remote sensing (Gao, 2015; Jawak et al., 2015). The Shuttle Radar Topography Mission (SRTM) has provided high-resolution (~30 m) global digital elevation models (DEMs) that could, in principal, present bathymetry of such desert lakes. Yet radar altimetry cannot produce accurate DEMs if the area is flooded or where lake floors are exceptionally bright and/or smooth (Berry et al., 2007; Brenner et al., 2007), which are common conditions.

To improve lake-bathymetry maps, recent studies either integrate remote-sensing data with a spatial interpolation of in situ measurements (Feng et al., 2011; Leon & Cohen, 2012) or combine between optical

imaging and radar (e.g., Sun & Ma, 2019) or laser altimetry (Arsen et al., 2013; Li et al., 2019; Ma et al., 2019). These satellite imaging methods are based on determining isobaths (equal depth lines) of a lake, through snapshots during different lake stages. Then, shorelines in each specific image are assigned a height through accurate elevation measurements; such as laser altimetry. This determines bathymetry only to the depth of the lowest shoreline identified, using a spatial interpolation of a few isobaths. It also overlooks the possible variance in elevation of a specific shoreline, which can be significant in large lakes (Arsen et al., 2013; Feng et al., 2011). Li et al. (2019) suggested using a long-term (410 images during >30 year) water occurrence index, instead of a few specific isobaths, and relating it with measurements from a limited data set of airborne lidar altimetry. This overcomes shoreline elevation variations and makes spatial interpolation unnecessary. However, they assumed a linear relation between isobath areas, sampled at specific points, and elevation. Applying their methodology to a deep reservoir (Lake Mead; >100-m deep) only revealed the bathymetry of the upper part of the lake; the deeper bathymetry was extrapolated with geometrical considerations, calibrated using in situ data (Li et al., 2019). A further complication arises where water occurrence is not based directly on elevation, primarily where a lake is composed of a few subbasins, which yields more than one possible relation between water occurrence and elevation. Accordingly, present-day methodologies and freely available data sets cannot provide accurate, high-resolution bathymetry of often-flooded, shallow desert lakes, especially for lakes having more than one subbasin.

Thus, to derive the bathymetry of desert lakes, there is a need for (a) an efficient and reliable way to recognize the water occurrence at a high resolution, (b) a technique to overcome diverse water occurrence-elevation relations in different subbasins, (c) a way to derive the bathymetry when lakes are inundated, and (d) a robust method to validate the resultant bathymetry. To tackle these challenges, we developed a simple and easily implemented methodology that derives bathymetry of shallow desert lakes. This paper focuses on three desert lakes, ranging in area from $0.2 \times 10^3 \text{ km}^2$ to $6 \times 10^3 \text{ km}^2$. Lake bathymetries are acquired using the relation between globally available high-resolution (30 m) water occurrence maps and elevation data from NASA's new Ice, Cloud, and Land Elevation Satellite-2 (ICESat-2).

Following is a description of the methodology and its application over Lake Eyre, which consists of a few subbasins. We show the derivation of a bathymetric map for the lake and validate it versus the global SRTM and the best bathymetric map available for the region (section 3). Having better results than the SRTM, we set to derive the bathymetry of a remote lake in the Sahara (Sabkhat El-Mellah) that has no other bathymetric map (section 4) and of Lago Coipasa in the Altiplano for which we separately derive the bathymetry under dry and inundated conditions.

2. Methodology

Desert lakes are often fed by floods with monthly to decadal frequencies. Most of the coarser particles are deposited upstream, and thus, lake floors are mainly covered with fine low-permeability sediments, making evaporation the primary output (Nicholson, 2011). Water occurrence in these lakes is <100% of the time and often <30%. Thanks to a detailed analysis of 3×10^6 Landsat images by Pekel et al. (2016), the frequency of water occurrence over 30-m pixels between 1984 and 2015 is easily accessible worldwide. Water occurs more often over the deeper parts of the lake, where complete evaporation takes longer, and less often over the higher lake margins. Thus, there should be a straightforward relation between water occurrences (i.e., the relative frequency of water in a pixel) and lake floor elevation over such lakes. This, in turn, allows measuring height over specific locations within the lake, from which we can infer the entire lake floor elevation.

ICESat-2 provides dense and accurate elevation measurements (0.7-m point spacing; accuracy and precision of <5 and < 13 cm, respectively) over land and even underwater. Thus, it yields accurate, narrow (~14 m) height profiles of Earth surface, since its launch in September 2018, with a 91-day revisiting frequency (Brunt et al., 2019; Markus et al., 2017). Underwater measurements can penetrate up to ~1 Secchi depth (Parrish et al., 2019), i.e., up to a few meters or even a few dozens of meters (Ma et al., 2019), depending on the optical properties of the water.

To derive bathymetry maps, we rely on the relation between Water Occurrence and Laser Profile elevation (hereon WOLP) using four (to five) steps (described schematically in Figure S1 in the supporting information): (a) acquiring a lake water occurrence map from the global water occurrence (Pekel et al., 2016), (b) extracting ICESat-2 elevation data (ATL03 product) that coincide with the lake (defined as regions with

Figure 1. An example of bathymetry derivation in Lake Eyre north (a schematic representation of this process is in Figure S1). (a) Water occurrence from Pekel et al. (2016) and 10 ICESat-2 scans over the lake (labeled) used to derive elevations. Scans are colored by the five identified pseudo-watersheds (Text S1). (b) The relation between water occurrence and elevation measurements from ICESat-2 scan #1 with a two-term Gaussian fit and its 95% prediction boundaries. Colors represent latitude. (c) The same as in b, but for scan #3. The fit here is divided according to the watersheds. (d) Derived bathymetry map based on the methodology presented in section 2. Gray dots represent regions in which water occurrence is greater than the highest occurrence overpassed by ICESat-2. B = Belt Bay. M = Madigan Gulf.

>0% water occurrence) (Figure 1a), (c) fitting a mathematical function describing the relation between water occurrence values and elevations (Figure 1b) based on all available scans in the lake extent, and (d) applying the fitted function areally, to translate the water occurrence map into lake-floor elevation over the entire lake basin (Figure 1d). For lakes consisting of subbasins, an additional step is needed between steps c and d, in which we identify lake subbasins from water occurrence, as detailed in section 3 (e.g., Figure 1c). This methodology provides a bathymetric map of lakes that were flooded to some extent between 1984 and 2015, with a resolution of ~30 m.

To evaluate our methodology, we use available topographic data to demonstrate differences between our results and available bathymetric (or topographic) maps. Where the SRTM is the best external source, we use cross-validation, putting aside one ICESat-2 scan each time and validating the bathymetry based on all other scans. Owing to the high accuracy of the ICESat-2 data, we demonstrate the small expected error using our methodology.

3. Lake Eyre

Lake Eyre (Figures 2c and 2e) has a watershed covering almost 1% of the global land area ($>1.1 \times 10^6$ km²). It has a complex lake floor with a minimum elevation of -15.2 m relative to the Australian Height Datum (Kotwicki & Isdale, 1991). The great flood of 1974 was utilized to perform bathymetric surveys over the lake, yielding a 0.5-m contour-interval bathymetric map and detailing features >1 km² (Bye et al., 1978). Leon and Cohen (2012) (hereon LC12) combined data from this bathymetric map with SRTM data and ICESat-1 laser altimetry (with 170-m point spacing) to form the best bathymetric map of the lake that we are aware of. Because of its vast size, complex bathymetry, and a good reference map, we chose to apply our methodology over Lake Eyre. To have a continuous map, we only mapped Lake Eyre North (the larger and more frequently flooded part of the lake).

To overcome complexity arising from the different relations of water occurrence and elevation in each of the subbasins (Figure 1b), we divided Lake Eyre North into five subbasins using the water occurrence map (Figures 1a and S2). This enabled identification of pseudo watersheds, similar to determining watersheds in a topographic map (Text S1; Schwanghart and Scherler (2014)). We then performed steps b to d of our methodology, separately for each subbasin (as exemplified in Figure 1c). If more than one ICESat-2 scan

Figure 2. Comparisons of WOLP bathymetries with SRTM data in (a) Lake Eyre, (d) Sabkhat El-Mellah, and (g) Lago Coipasa. (b) Comparison of Lake Eyre bathymetry with the map of Leon and Cohen (2012). (e) Location map of the three lakes and aridity index (UNEP, 1992) from the climatic research unit of the University of East Anglia (New et al., 2002). (c, f, and i) True-color satellite imagery of the lakes from Esri/Digitalglobe and maximum extent of water occurrence in black from Pekel et al. (2016). (h) Difference between the “wet” and “dry” bathymetries of Lago Coipasa.

intersected a watershed, we used data from all available scans. To form a single map out of the different subbasins, regions close to the pseudo water divide were assigned values using step c from all neighboring subbasins, inversely weighted according to their distance from the divide (Text S1).

We validated the WOLP bathymetry map (Figure 1d) against SRTM data and the LC12 bathymetry over the entire region (Table 1, Figures 2a and 2b) and against ICESat-2 scans over the measured profiles (Figure S3). The WOLP bathymetry lies within ± 0.5 m of LC12 elevations for 74% of the region (90% is within ± 1 m); i.e., it lies within one elevation contour of Bye et al. (1978). Most of the remaining areas (deviating > 1 m) are situated next to the lake margins, where the LC12 map is mostly based on SRTM data, which were acquired during a lake inundation interval and are therefore not reliable over major parts of the lake (Leon & Cohen, 2012). In $\sim 83\%$ of the area, SRTM data were replaced by a constant elevation value (-15 m, Australian Height Datum). The root mean square difference (RMSD) of the SRTM data versus the LC12 map is 1.77 m, and only 25% of the SRTM data are within ± 0.5 m of LC12, whereas the WOLP bathymetry has a RMSD of 0.52 m (Table 1). Moreover, the mean RMSD for each of the subbasins using cross-validation of the different ICESat-2 scans is 0.21–0.57 m (Figure S4), indicating that the WOLP map error is even smaller than it seems when comparing it to the LC12 map.

Hypsometric curves emphasize differences between these analyzed bathymetries (Figure 3) and are important for water volume estimates (Text S2). Whereas the SRTM wet area sharply increases above the

Table 1
Validation Results Across the Lakes

Lake	Validated map	Reference	Regional/profile validation	RMSD (m)	Lake depth (m)
Lake Eyre	SRTM	LC12	Regional	1.77	3.2 (WOLP) ^c , 4.1 (LC12) ^c
	WOLP (this study)	LC12	Regional	0.52	
	SRTM	ICESat-2	Profile	0.95–2.30 ^a	
	LC12	ICESat-2	Profile	0.20–0.69 ^{ac}	
	WOLP	ICESat-2	Profile, cross-validation	0.21–0.57 ^a	
Sabkhat El-Mallah	SRTM	ICESat-2	Profile	2.04 ^b	5.0 (WOLP) ^c
	WOLP	ICESat-2	Profile, cross-validation	0.32 ^b	
	SRTM	ICESat-2	Profile	2.84 ^b	
Lago Coipasa	WOLP (“dry”)	ICESat-2	Profile, cross-validation	0.28 ^b	1.2 (WOLP: “dry”) ^c
	WOLP (“wet”)	WOLP (“dry”)	Regional	0.39	
	WOLP (“wet”)	ICESat-2	Profile, cross-validation	0.47 ^b	2.2 (WOLP: “wet”) ^c
	WOLP (“wet”)	ICESat-2	Profile, cross-validation	0.47 ^b	

^cRange denotes the average RMSD for each subbasin, averaged between the different ICESat-2 profiles in it. ^aAverage among the different ICESat-2 profiles.

^bEstimated (see Text S2).

minimum elevation, because of the constant (−15 m) elevation polygon, the WOLP and the LC12 wet area curves present a gradual increase with depth (Figure 3a). Accordingly, water volumes are lower by ~75% both in the WOLP and LC12 bathymetries compared to the SRTM. Both the WOLP and the LC12 exhibit similar hypsometry in depths of <1 m (dissimilar to the SRTM). According to these maps, the southwestern subbasin (Belt Bay) is the first to be filled (in accordance with MODIS imagery of floods, Movie S1). Differences between WOLP and LC12 bathymetries increase above lake depths of 1 m, when the southeastern subbasin (Madigan Gulf) fills according to WOLP bathymetry. In the LC12 map, the sill between the southern subbasins is higher, and therefore, the flooded area increases only above water depth of 2 m. Large differences exist between WOLP and LC12 at the lake's margins; there, LC12 bathymetry rises ~5 m above the lake bottom (Figure 3a). These differences seem to be related to the SRTM-dependent mapping of the lake margins in LC12. At a depth of 3.1 m, the WOLP flooded area reaches its maximum extent, featuring an area of $6.1 \times 10^3 \text{ km}^2$ and a volume of 8.9 km^3 , ~33% higher than the respective area and volume calculated based on the LC12 map (Figure 3a). Nevertheless, it is important to note that WOLP bathymetry represents only regions that were flooded between 1984 and 2015 and that the largest flood in recent history occurred in the 1970s. Therefore, higher shorelines, as in LC12 or Cohen et al. (2018), could not be mapped with WOLP.

4. Application for Nonmapped and Inundated Lakes

Sabkhat El-Mallah is a small, northwestern Sahara ephemeral lake (~170 km²) (Figures 2e and 2f). It is fed in the High Atlas Mountains and is flooded only once every few years (Mabbutt, 1977). There is no bathymetric map of this lake that we are aware of. A comparison of the WOLP bathymetry (Figure S5) to the SRTM data (Figures 2d and S6) indicates generally a similar pattern (location of the deepest part of the lake and its margins, large scale slopes, etc.). However, variations of the SRTM data over Sabkhat El-Mallah are approximately $\pm 2 \text{ m}$ (Figures 3b and S6), while lake depth is ~5 m, yielding an uncharacteristic discontinuous and rough lake floor (e.g., Quade et al., 2018). The mean cross-validation RMSD of WOLP bathymetry is much lower (0.32 m; Table 1, Figure S7). The WOLP map exhibits a much higher flooded area in comparison with the SRTM data (Figure 3b). E.g., at a 1-m lake depth, the WOLP lake area is $0.15 \times 10^3 \text{ km}^2$ versus $0.08 \times 10^3 \text{ km}^2$ according to SRTM data.

The same methodology was applied over Lago Coipasa (or Salar de Coipasa; surface area up to 2,400 km²), which is a high altitude (3,660 m), shallow saline lake, occasionally filled with water (Placzek et al., 2006) (Figures 2e and 2i). However, during February 2019, the lake was flooded (Movie S2); thus, ICESat-2 scans taken afterward exhibit both the water surface and the lake floor in its inundated region.

Recent studies highlight the ability of ICESat-2 scans to penetrate water and yield bathymetric profiles (Forfinski-Sarkozi and Parrish, 2016; Ma et al., 2019; Parrish et al., 2019). Therefore, we derived two different bathymetric maps of Lago Coipasa, one using all available “dry” scans (i.e., before February 2019; Figure S8) and the other (Figure S9) using only post-flood scans (“wet” scans), manually omitting the ICESat-2's water

Figure 3. Hypsometric curves, extent maps and cross-sections for (a) Lake Eyre, (b) Sabkhat El-Mellah, and (c) Lago Coipasa. The maps show filling extent at heights (denoted by a gray line on the hypsometric curves) that exert major differences between bathymetries. Details of the preparation of the hypsometries are in Text S2.

surface readings (Text S3). The difference between the “dry” bathymetry and the SRTM data and the

difference between the “dry” and “wet” maps are shown in Figures 2g and 2h, respectively. Given the difficulty in determining water density, we did not correct the effect of the changing refraction coefficient between water and air on underwater elevation measurements. However, to avoid location errors, we used only nadir data, which are expected to have the least spatial error. The expected vertical error where water depth is ~ 0.7 m (Text S3), as in this 2019 flood, is <0.18 m (Parrish et al., 2019) or even less (as shown in Ma et al., 2019).

Similar to Lake Eyre, the WOLP-SRTM difference map (Figure 2g) illustrates that Lago Coipasa was inundated during the SRTM scan, and the wet part of the scan was replaced with a fixed elevation value. The SRTM data over the lake area varies within $\sim \pm 5$ m (RMSD = 2.84 m; Figures 3c and S10), meaning that over a ~ 1.5 -m deep lake, such as Lago Coipasa, SRTM-based water volume calculations for all practical matters are absurd. In contrast, both the “dry” and the “wet” WOLP bathymetries yield a much smaller mean cross-validation RMSD value (0.28 and 0.47 m, respectively; Table 1, Figures S11 and S12).

The fixed-elevation polygon in the SRTM data for Lago Coipasa is bounded by high (>2 m) artificial walls. This is exhibited in the hypsometry by a sharp increase and then a fixed wetted area of 0.87×10^3 km² (Figure 3c). In lake depths of <1 m, the “dry” bathymetry presents a detailed gradual increase in lake area and volume, filling most of the maximum lake extent. The “wet” WOLP area at 1-m depth is smaller than the “dry” area due to a 1.3-m deeper lake bottom in the “wet” bathymetry (Figure 3c; Text S2). Both the “dry” and “wet” scans did not cross the northernmost part of the lake, which is characterized by the highest water occurrence (and presumably deepest water column). For this reason, we stress that future crossing of ICESat-2 over this specific region of the lake could improve its bathymetry.

Compared with the “dry” bathymetry, 58% of the “wet” lake area lies within ± 0.5 m of the “dry” bathymetry (RMSD = 0.39 m). Thus, relying on the “dry” bathymetric map, which seems reasonable in light of the results shown for Lake Eyre, we suggest that even when using only the “wet” scans, the WOLP bathymetry yields better results than the currently available global product (SRTM). This leads us to propose the usage of the methodology presented here for any of the world’s shallow desert lakes.

5. Discussion

The largest source of uncertainty in the WOLP bathymetry stems from the selected fitting equation between water occurrence and elevation (step c). However, this selection affects mainly the extremities of data, i.e., the extrapolation of elevation to values that were not observed by the ICESat-2 (areas with gray dots in Figures 1c, S5, S8 and S9). Thus, in cases where ICESat-2 data cover the water frequency extremities, WOLP bathymetry is accurate, as demonstrated by the cross-validation results. Large enough lakes should be covered by at least a few ICESat-2 scans (e.g., Figure 1a), and therefore, scans are expected to cover a wide range of water occurrences. This wide range can yield an accurate bathymetry for almost all of the lake extent.

Laser altimetry errors, estimated to be ~ 0.3 m for a single photon return, and much lower (0.05–0.07 m) for an average of neighboring photon returns (Jasinski et al., 2016), are not expected to impact our results significantly. A larger uncertainty lies between points that have a similar water occurrence but different elevation, as is the case if there are small and local topographic minima. Using more scans may decrease the variations, although some of them may be intrinsic, e.g., where transmission losses or springs are common. Water occurrence minima can be too small to be identified as a different subbasin. Thus, our method is limited to subbasins that are large enough to be resolved with ICESat-2, as in Lake Eyre (Figure 1 and Text S1). In deriving the Lake Eyre bathymetry, we used at least four scans for each subbasin, yielding an error of only 0.2–0.6 m (Table 1, Figure S4).

Another limitation to our methodology comes from the maximum water penetration of the ICESat-2 laser. This limits the ability to derive bathymetry in lakes that have a water depth of tens of meters or more. In such circumstances, a partial bathymetry could still be derived for the outskirts of the lakes using our methodology, or as presented in Li et al. (2019) or in Ma et al. (2019) for the shoulders of Lake Mead. However, we focus here on shallow desert lakes, in which, by definition, this is not a major obstacle.

Sediment deposition could also increase the uncertainty of the derived bathymetry. Here, we use satellite imaging water occurrence from >30 -year period (Pekel et al., 2016), implying that if the lake floor was

altered during this time interval, present-day ICESat-2 scans can yield only an averaged bathymetry of this period. However, newer global water occurrence data sets could emerge in the near future, enabling both derivation of newer bathymetries, and higher resolution maps (e.g., 10–20-m pixels from Sentinel-2).

Apart from these limitations, taking a long series of satellite imagery extends a great opportunity. If only specific dates are used to identify isobaths (or shorelines), the error propagates to the bathymetric map. Using statistics based on many years, single-image errors diminish. Such errors include water piling up on one side of the lake due to winds (Arsen et al., 2013), misclassification of water boundaries or crossing isobaths (Long et al., 2019), and specific date imaging having only partial coverage of a lake, because of imaging geometry or cloud obscuration. Moreover, the use of specific date imagery requires a spatial interpolation between isobaths, thus concealing small features in between isobaths.

Out of the three lakes analyzed above, Lake Eyre is probably the most closely monitored, yet the nearest river gauge is situated many hundreds of kilometers upstream. Therefore, there is no accurate in situ data for water input volumes. ICESat-2's high spatial resolution (~70 cm) combined with high-resolution water occurrence map (e.g., 30 m in the map of Pekel et al., 2016) yields an accurate, high-resolution bathymetry, even over flooded or complex desert lakes. Such maps could help in determining the water discharge into remote desert lakes and their evaporative losses, providing much-needed data in remote areas, serving as a basis for mass and energy balance calculations over such lakes and for water management strategies.

6. Conclusions

Using a new methodology which links long-term water occurrence and accurate height measurements, each independently derived from satellite remote sensing, we mapped the bathymetry of three shallow lakes in drylands across the globe. We verified the bathymetries using a previous bathymetric map, SRTM data, and through cross-validation. This easy-to-implement methodology yields a high-resolution bathymetry of shallow desert lakes that were flooded sometime during 1984–2015, using globally available data sets.

1. As an example of a complex shallow lake system, we used Lake Eyre, consisting of multiple subbasins. Despite its complexity, verification versus the best available DEM showed that the methodology is successful, as long as each subbasin is covered by an elevation measurement scan.
2. The methodology was also applied to two lakes with no previous bathymetry maps, one in the Sahara (Sabkhat El-Mellah) and the other in the Altiplano (Lago Coipasa). Results proved low cross-validation RMSD values (~0.3 m) compared with the SRTM data (~2.5 m).
3. Applying the methodology in Lago Coipasa separately to “dry” and to “wet” ICESat-2 scans, relying on laser penetrability, we showed that bathymetry can even be produced during lake inundation.

The presented methodology can be applied to a large portion of the shallow lakes around the globe. It enables mapping of inundated lakes (a major obstacle for widely used methods), small lakes, and large and complex lake systems.

Acknowledgments

This research was supported by ISF grant 946/18 and NSFC-ISF grant 2487/17 to YE. Water occurrence data (Pekel et al., 2016) were obtained from <https://global-surface-water.appspot.com>, using Google Earth Engine (<https://earthengine.google.com/>). ICESat-2 ATL03 data were obtained from <https://openaltimetry.org/data/icesat2/>: Neumann, T. A., A. Brenner, D. Hancock, J. Robbins, J. Saba, K. Harbeck, and A. Gibbons. 2019. ATLAS/ICESat-2 L2A Global Geolocated Photon Data, V1. [ATL03]. Boulder, Colorado USA. NSIDC: National Snow and Ice Data Center. doi: <https://doi.org/10.5067/ATLAS/ATL03.001>. [Dec 2019]. The authors declare no conflict of interests.

References

- Arsen, A., Crétau, J. F., Berge-Nguyen, M., & del Rio, R. A. (2013). Remote sensing-derived bathymetry of Lake Poopó. *Remote Sensing*, 6(1), 407–420. <https://doi.org/10.3390/rs6010407>
- Berry, P. A. M., Garlick, J. D., & Smith, R. G. (2007). Near-global validation of the SRTM DEM using satellite radar altimetry. *Remote Sensing of Environment*, 106(1), 17–27. <https://doi.org/10.1016/j.rse.2006.07.011>
- Brenner, A. C., DiMarzio, J. P., & Zwally, H. J. (2007). Precision and accuracy of satellite radar and laser altimeter data over the continental ice sheets. *IEEE Transactions on Geoscience and Remote Sensing*, 45(2), 321–331. <https://doi.org/10.1109/TGRS.2006.887172>
- Brunt, K. M., Neumann, T. A., & Smith, B. E. (2019). Assessment of ICESat-2 ice sheet Surface Heights, based on comparisons over the interior of the Antarctic ice sheet. *Geophysical Research Letters*, 46, 13,072–13,078. <https://doi.org/10.1029/2019GL084886>
- Bye, J. A. T., Dillon, P. J., Vandenberg, J. C., & Will, G. D. (1978). Bathymetry of Lake Eyre. *Transactions and Proceedings of the Royal Society of South Australia*, 102(1), 85–89. <https://doi.org/10.1080/00359196009519029>
- Cohen, T. J., Jansen, J. D., Gliganic, L. A., Larsen, J. R., Nanson, G. C., May, J. H., et al. (2015). Hydrological transformation coincided with megafaunal extinction in central Australia. *Geology*, 43(3), 195–198. <https://doi.org/10.1130/G36346.1>
- Cohen, T. J., Meyer, M. C., & May, J. H. (2018). Identifying extreme pluvials in the last millennia using optical dating of single grains of quartz from shorelines on Australia's largest lake. *Holocene*, 28(1), 150–165. <https://doi.org/10.1177/0959683617715700>
- Crétau, J. F., Abarca-del-Río, R., Bergé-Nguyen, M., Arsen, A., Drolon, V., Clos, G., & Maisongrande, P. (2016). Lake volume monitoring from space. *Surveys in Geophysics*, 37(2), 269–305. <https://doi.org/10.1007/s10712-016-9362-6>
- D'Odorico, P., & Porporato, A. (2006). *Dryland ecohydrology*. Dordrecht, The Netherlands: Springer.
- de Martonne, E. (1927). Regions of interior-basin drainage. *Geographical Review*, 17(3), 397–414.

- Enzel, Y., & Wells, S. G. (1997). Extracting Holocene paleohydrology and paleoclimatology information from modern extreme flood events: An example from southern California. *Geomorphology*, 19(3–4), 203–226. [https://doi.org/10.1016/s0169-555x\(97\)00015-9](https://doi.org/10.1016/s0169-555x(97)00015-9)
- Feng, L., Hu, C., Chen, X., Li, R., Tian, L., & Murch, B. (2011). MODIS observations of the bottom topography and its inter-annual variability of Poyang Lake. *Remote Sensing of Environment*, 115(10), 2729–2741. <https://doi.org/10.1016/j.rse.2011.06.013>
- Forfinski-Sarkozi, N. A., & Parrish, C. E. (2016). Analysis of MABEL bathymetry in Keweenaw Bay and implications for ICESat-2 ATLAS. *Remote Sensing*, 8(9). <https://doi.org/10.3390/rs8090772>
- Gao, H. (2015). Satellite remote sensing of large lakes and reservoirs: From elevation and area to storage. *Wiley Interdisciplinary Reviews Water*, 2(2), 147–157. <https://doi.org/10.1002/wat2.1065>
- Jasinski, M. F., Stoll, J. D., Cook, W. B., Ondrusek, M., Stengel, E., & Brunt, K. (2016). Inland and near-shore water profiles derived from the high-altitude multiple altimeter beam experimental Lidar (MABEL). *Journal of Coastal Research*, 76(sp1), 44–55. <https://doi.org/10.2112/si76-005>
- Jawak, S. D., Vadlamani, S. S., & Luis, A. J. (2015). A synoptic review on deriving bathymetry information using remote sensing technologies: Models, methods and comparisons. *Advances in Remote Sensing*, 04(02), 147–162. <https://doi.org/10.4236/ars.2015.42013>
- Kotwicki, V., & Isdale, P. (1991). Hydrology of Lake Eyre, Australia: El Niño link. *Palaeogeography Palaeoclimatology Palaeoecology*, 84(1–4), 87–98. [https://doi.org/10.1016/0031-0182\(91\)90037-R](https://doi.org/10.1016/0031-0182(91)90037-R)
- Leon, J. X., & Cohen, T. J. (2012). An improved bathymetric model for the modern and palaeo Lake Eyre. *Geomorphology*, 173–174, 69–79. <https://doi.org/10.1016/j.geomorph.2012.05.029>
- Li, Y., Gao, H., Jasinski, M. F., Zhang, S., & Stoll, J. D. (2019). Deriving High-Resolution Reservoir Bathymetry From ICESat-2 Prototype Photon-Counting Lidar and Landsat Imagery. *IEEE Transactions on Geoscience and Remote Sensing*, 1–11. <https://doi.org/10.1109/tgrs.2019.2917012>
- Long, Y., Yan, S., Jiang, C., Wu, C., Tang, R., & Hu, S. (2019). Inversion of Lake bathymetry through integrating multi-temporal Landsat and ICESat imagery. *Sensors*, 19(13), 2896. <https://doi.org/10.3390/s19132896>
- Ma, Y., Xu, N., Sun, J., Wang, X. H., Yang, F., & Li, S. (2019). Estimating water levels and volumes of lakes dated back to the 1980s using Landsat imagery and photon-counting lidar datasets. *Remote Sensing of Environment*, 232(July), 111,287. <https://doi.org/10.1016/j.rse.2019.111287>
- Mabbutt, J. A. (1977). *Desert landforms*, (Second pri ed.). Cambridge, Massachusetts, USA: The MIT Press.
- Markus, T., Neumann, T., Martino, A., Abdalati, W., Brunt, K., Csatho, B., et al. (2017). The Ice, Cloud, and Land Elevation Satellite-2 (ICESat-2): Science requirements, concept, and implementation. *Remote Sensing of Environment*, 190, 260–273. <https://doi.org/10.1016/j.rse.2016.12.029>
- New, M., Lister, D., Hulme, M., & Makin, I. (2002). A high-resolution data set of surface climate over global land areas. *Climate Research*, 21(1), 1–25. <https://doi.org/10.3354/cr021001>
- Nicholson, S. E. (2011). *Dryland climatology*. New York: Cambridge University Press.
- Noy-Meir, I. (1973). Desert ecosystems: Environment and producers. *Annual Review of Ecology and Systematics*, 4, 25–51.
- Parrish, C. E., Magruder, L. A., Neuenschwander, A. L., Forfinski-Sarkozi, N., Alonzo, M., & Jasinski, M. (2019). Validation of ICESat-2 ATLAS bathymetry and analysis of ATLAS's bathymetric mapping performance. *Remote Sensing*, 11(14), 1634. <https://doi.org/10.3390/rs11141634>
- Pekel, J. F., Cottam, A., Gorelick, N., & Belward, A. S. (2016). High-resolution mapping of global surface water and its long-term changes. *Nature*, 540(7633), 418–422. <https://doi.org/10.1038/nature20584>
- Placzek, C., Quade, J., & Patchett, P. J. (2006). Geochronology and stratigraphy of late Pleistocene lake cycles on the southern Bolivian Altiplano: Implications for causes of tropical climate change. *Bulletin Geological Society of America*, 118(5–6), 515–532. <https://doi.org/10.1130/B25770.1>
- Quade, J., Dente, E., Armon, M., Ben Dor, Y., Morin, E., Adam, O., & Enzel, Y. (2018). Megalakes in the Sahara? A review. *Quaternary Research (United States)*, 90(2), 253–275. <https://doi.org/10.1017/qua.2018.46>
- Schwanghart, W., & Scherler, D. (2014). Short communication: TopoToolbox 2 - MATLAB-based software for topographic analysis and modeling in earth surface sciences. *Earth Surface Dynamics*, 2(1), 1–7. <https://doi.org/10.5194/esurf-2-1-2014>
- Sun, F., & Ma, R. (2019). Hydrologic changes of Aral Sea: A reveal by the combination of radar altimeter data and optical images. *Annals of GIS*, 25(3), 247–261. <https://doi.org/10.1080/19475683.2019.1626909>
- UNEP (1992). *World atlas of desertification*. London: Edward Arnold, London.