



UNIVERSITY
OF WOLLONGONG
AUSTRALIA

University of Wollongong
Research Online

Faculty of Science, Medicine and Health - Papers

Faculty of Science, Medicine and Health

2011

Influence of gap fraction on coniferous needle optical properties measurements

Lucia Yanez-Rausell
Wageningen University

Zbynek Malenovsky
University of Zurich, zbynek@uow.edu.au

Michael E. Schaepman
University of Zurich

Publication Details

Yanez-Rausell, L., Malenovsky, Z. & Schaepman, M. (2011). Influence of gap fraction on coniferous needle optical properties measurements. Abstract Volume 9th Swiss Geoscience Meeting: 18. 8. Advances in GIScience and Remote Sensing (pp. 391-391). Zurich, Switzerland: SCNAT.

Research Online is the open access institutional repository for the University of Wollongong. For further information contact the UOW Library: research-pubs@uow.edu.au

Influence of gap fraction on coniferous needle optical properties measurements

Abstract

Abstract of presentation at the 9th Swiss Geoscience Meeting, Zurich 2011, 11-13 November, ETH Hauptgebaude & Department of Earth Sciences, ETH Zurich.

Disciplines

Medicine and Health Sciences | Social and Behavioral Sciences

Publication Details

Yanez-Rausell, L., Malenovsky, Z. & Schaepman, M. (2011). Influence of gap fraction on coniferous needle optical properties measurements. Abstract Volume 9th Swiss Geoscience Meeting: 18. 8. Advances in GIScience and Remote Sensing (pp. 391-391). Zurich, Switzerland: SCNAT.

P 18.7

Influence of gap fraction on coniferous needle optical properties measurements

Yáñez-Rausell Lucía^{1,2}, Malenovský Zbynek², Schaepman Michael²

¹Centre for Geo-Information, Wageningen University, Droevendaalsesteeg 3/PO Box 47, 6700 AA Wageningen, The Netherlands
(lucia.yanezrausell@geo.uzh.ch)

²RSL, Department of Geography, Univ. of Zurich, Winterthurerstrasse 190, CH-8057 Zurich, Switzerland

Optical properties (OPs) of non-flat narrow leaves, i.e. coniferous needles, are extensively used by the remote sensing community, e.g. for calibration and validation of radiative transfer models at both leaf and canopy levels. Measurement of such small elements is, however, a technical challenge with a very little knowledge about related errors. Consequently two situations appear among the users of OPs: 1) the lack of such measurements forces them to make assumptions with a potentially negative impact on the interpretation of remote sensing data of coniferous forests (e.g. in radiative transfer modelling, needle transmittance is often assumed to be zero, or needle reflectance and transmittance are assumed to be equal); or 2) the used available datasets are of unknown reliability. This demonstrates a need for a robust, efficient and systematic measuring technique of narrow-leaf OPs.

Compared to the broad leaves, measurement of reflectance (R) and transmittance (T) of narrow leaves require adapting the conventional techniques (i.e. coupling a spectroradiometer to an integrating sphere) to a sample size smaller than the area illuminated by the incident light beam. Reduction of the illuminated area to the dimensions of one narrow leaf would result in a very low signal-to-noise performance. An alternative solution is to measure the signal from several needles simultaneously mounted next to each other in a carrier, and to correct such measurement for the portion of photons passing through the air gaps (gap fraction of the illuminated area – GF). The objective of this paper is to estimate an error budget of this technique by analysing errors originating from: 1) use of the carrier, 2) gap fraction estimation via digital image processing, and 3) multiple scattering caused by the non-flat nature of the needle leaves. To achieve this we measured OPs from an optically stable silicon material, which was cut in 1 mm thick strips to simulate needle shaped leaves. We build on the results presented by Mesarch et al. (1999) in which this technique was applied only on flat film paper, and we investigated the influence of the non-flat objects (needle leaves) on accuracy of the measurements. Computed R and T for different tested settings (i.e. carrier combinations, image processing settings, and distances between measured needles) were analysed to point out the best configurations and to estimate errors introduced by this technique.

REFERENCES

Mesarch, M.A., Walter-Shea, E.A., Asner, G.P., Middleton, E.M. & Chan, S.S. 1999: A revised measurement methodology for conifer needles spectral optical properties: evaluating the influence of gaps between elements. *Remote Sensing of Environment*, 68, 177–192.