University of Wollongong

Research Online

Faculty of Engineering and Information
Sciences - Papers: Part B

Faculty of Engineering and Information
Sciences

2019

Mining phosphorus from anaerobically treated dairy manure by forward osmosis membrane

Biplob K. Pramanik

Royal Melbourne Institute of Technology, biplobkp@uow.edu.au

Faisal I. Hai

University of Wollongong, faisal@uow.edu.au

Ashley Ansari

University of Wollongong, ashleyz@uow.edu.au

Felicity Roddick

Royal Melbourne Institute of Technology

Follow this and additional works at: <https://ro.uow.edu.au/eispapers1>

Part of the [Engineering Commons](#), and the [Science and Technology Studies Commons](#)

Research Online is the open access institutional repository for the University of Wollongong. For further information contact the UOW Library: research-pubs@uow.edu.au

Mining phosphorus from anaerobically treated dairy manure by forward osmosis membrane

Abstract

We investigated the effect of draw solution type on the forward osmosis (FO) performance for enriching nutrients from anaerobically treated dairy manure (ATDM) followed by chemical precipitation for phosphorus recovery as struvite crystal. The FO membrane significantly rejected COD (>97%) and phosphate (>98%) whereas there was only 70%-73% and 73%-76% rejection of ammonia-nitrogen and total nitrogen, respectively. The draw solution type had little impact on the retention of the aforementioned wastewater constituents by the FO membrane. At 60% water recovery, a water flux decline of 82%-96% was observed due to increasing contaminant concentration in the concentrated feed solution. Water flux decline was less for MgCl₂ than EDTA-2Na and NaCl as draw solutes. On the contrary, the reverse solute flux was higher for NaCl than MgCl₂, which in turn was higher than EDTA-2Na. Pre-concentration of ATDM by FO facilitated struvite precipitation. MgCl₂ as the draw solute provided a higher purity of struvite than EDTA-2Na and NaCl. This is because when MgCl₂ was used as the draw solute, the reverse salt flux of magnesium to the concentrated ATDM provided favourable conditions for struvite crystal formation. This study demonstrates the technical feasibility of phosphorus recovery from ATDM using the FO process.

Disciplines

Engineering | Science and Technology Studies

Publication Details

Pramanik, B. Kumar., Hai, F. I., Ansari, A. J. & Roddick, F. A. (2019). Mining phosphorus from anaerobically treated dairy manure by forward osmosis membrane. *Journal of Industrial and Engineering Chemistry*, 78 425-432.

Research Highlights

- ❖ Phosphorus recovery from dairy manure using the FO process is demonstrated
- ❖ A water flux decline of 82-96% was observed at 60% water recovery by FO
- ❖ Water flux decline was less for MgCl_2 than EDTA-2Na and NaCl as draw solutes
- ❖ MgCl_2 as a draw solute provided a higher purity of struvite than EDTA-2Na and NaCl
- ❖ Draw solution has little effect on the retention of the contaminants by the FO membrane

Mining phosphorus from anaerobically treated dairy manure by forward osmosis
membrane

Biplob Kumar Pramanik^{a*}, Faisal I. Hai^b, Ashley J. Ansari^b, Felicity A. Roddick^a

^aSchool of Engineering, RMIT University, Melbourne, VIC 3000, Australia

^bStrategic Water Infrastructure Laboratory, School of Civil, Mining and Environmental
Engineering, University of Wollongong, Wollongong, NSW 2522, Australia

Corresponding author Email: biplob.pramanik@rmit.edu.au;

Telephone number: +613 9925 9419

Abstract

We investigated the effect of draw solution type on the forward osmosis (FO) performance for enriching nutrients from anaerobically treated dairy manure (ATDM) followed by chemical precipitation for phosphorus recovery as struvite crystal. The FO membrane significantly rejected COD (>97%) and phosphate (>98%) whereas there was only 70%-73% and 73%-76% rejection of ammonia-nitrogen and total nitrogen, respectively. The draw solution type had little impact on the retention of the aforementioned wastewater constituents by the FO membrane. At 60% water recovery, a water flux decline of 82%-96% was observed due to increasing contaminant concentration in the concentrated feed solution. Water flux decline was less for MgCl_2 than EDTA-2Na and NaCl as draw solutes. On the contrary, the reverse solute flux was higher for NaCl than MgCl_2 , which in turn was higher than EDTA-2Na. Pre-concentration of ATDM by FO facilitated struvite precipitation. MgCl_2 as the draw solute provided a higher purity of struvite than EDTA-2Na and NaCl. This is because when MgCl_2 was used as the draw solute, the reverse salt flux of magnesium to the concentrated ATDM provided favourable conditions for struvite crystal formation. This study demonstrates the technical feasibility of phosphorus recovery from ATDM using the FO process.

Keywords: Anaerobically treated dairy manure, draw solution, forward osmosis, contaminants rejection, struvite recovery

1. Introduction

Management of dairy manure represents one of the significant challenges for the development of the livestock industry due to the production of large volumes of wastewater

1 characterised by high organic and nutrient contents [1]. Discharge of the nutrients *i.e.*,
2 nitrogen and phosphorous into the aquatic environment is undesirable as they are the key
3 sources of eutrophication in the water environment. On the other hand, both phosphorus and
4 nitrogen are necessary for agricultural production [2]. Dairy manure has a high nutrient
5 content with typical phosphorus concentration varying from 50 mg/L to 350 mg/L [3, 4].
6 Hence the concept of recovering phosphorus from dairy manure is a 'renewable' alternative
7 for delivering sustainable phosphorus supplies as well as complying with the increasingly
8 stringent effluent discharge regulations.
9

10 Phosphorus has usually been recovered as struvite crystal ($\text{MgNH}_4\text{PO}_4 \cdot 6\text{H}_2\text{O}$) via chemical
11 precipitation [5, 6] from different sources such as wastewater [7], anaerobically digested
12 sludge [8-10], and urine [11]. Recently, Oliveira et al. [12] investigated phosphorous
13 extraction from dairy manure. Notably, a pre-treatment is required to solubilise the
14 phosphorus content in dairy manure in order to implement the struvite precipitation process.
15 This is because 65-70% of the phosphorus in dairy manure occurs in particulate form [13,
16 14]. To solubilise the particulates, dairy manure can mainly be anaerobically pre-treated
17 before struvite recovery [15]. Irrespective of the pre-treatment, magnesium ion needs to be
18 added to the solution to induce precipitation of phosphorous in the form of struvite.
19

20 Recent studies have investigated the forward osmosis (FO) process for the pre-concentration
21 of wastewater for nutrient recovery [16]. It is an osmotically-driven process in which water
22 passes from a solution of lower osmotic pressure into a solution of higher osmotic pressure
23 [17]. The solution of higher osmotic pressure is known as the draw solution. The FO process
24 has a number of benefits such as high contaminant rejection and lower fouling tendency
25 compared to conventional pressure-driven membrane processes [18-20]. While producing
26

clean water, this process can concentrate phosphate, magnesium and ammonium in the feed side to enable struvite recovery [21]. A few studies have investigated the FO process for phosphorus recovery from municipal wastewater [22, 23], urine [24] and digested sludge centrate [21, 25]. However, no study has explored the application of FO for enriching phosphorus concentration for struvite recovery from dairy manure.

Reverse solute flux is a critical phenomenon in the FO process. Ions with various diffusivities in feedwater can influence the charge characteristics of the FO membranes because of adsorption and electrostatic interactions, resulting in different extent of reverse solute flux *i.e.*, passage of draw solute back into the feed side. Studies have investigated the impact of draw solute type on reverse solute flux during wastewater treatment by FO. Inorganic salts are commonly used as draw solutes as they are inexpensive, can create high osmotic pressure, and pose less likelihood of inducing significant internal concentration polarisation (ICP) due to their rapid diffusion and small solute size. However, these characteristics typically provide a high reverse solute flux [26]. It is noteworthy that most of the previous studies have used only one type of draw solute for the nutrient recovery. For example, Zhang et al. [24] and Xue et al. [22] used seawater brine as a draw solution for mining nutrient from municipal wastewater and urine, respectively. Xie et al. [21] used magnesium chloride as a draw solution for struvite recovery from anaerobically digested sludge centrate. Hence, the potential impacts of reverse solute flux on clean water flux and struvite recovery from dairy manure while using different draw solutes remain to be elucidated.

The purpose of this research was to investigate the application of the FO system for recovering phosphorus from anaerobically treated dairy manure effluent by integrating the process with a chemical precipitation technique. The effect of three different commonly used

draw solutions, on FO performance was evaluated in terms of water flux, bulk organics removal and phosphate mineral recovery as struvite crystal.

2. Materials and Methods

2.1. Collection of feed solution

The dairy wastewater was collected from a commercial dairy farm in Gerringong, Wollongong, Australia. At that site, the dairy wastewater is treated by anaerobic and then aerobic ponds. Then the biologically treated effluent is released to the sewer network for further treatment at the municipal wastewater treatment plant. In this study, initially three different samples, namely, raw dairy wastewater, anaerobic pond effluent and aerobic pond effluent, were investigated. Finally, anaerobic pond effluent was used for struvite recovery, and the reason for this choice is discussed in Section 2.2. All wastewater samples were stored at 4 °C. Before all tests, wastewater samples were filtered through a 100 µm membrane and brought to laboratory temperature (22±2 °C).

2.2. Characteristics of the dairy manure

Data on the chemical composition of the raw dairy manure, and the anaerobic and aerobic pond effluent streams are summarised in Table 1. The concentrations of the monitored parameters in the investigated dairy manure were comparable to that in previous studies [27, 28]. Effluent from both ponds exhibited substantially reduced concentration of COD with a COD removal efficiency of 62% and 75% after anaerobic and aerobic treatment, respectively. The pre-treated wastewater had a higher pH than the raw wastewater. There was no removal of inorganic contents by either pond.

Overall about 50% removal of $\text{NH}_3\text{-N}$ was achieved. This can be attributed to biological nitrification, assimilation and/or $\text{NH}_3\text{-N}$ loss due to the increased pH and the uncovered surface of the pond, promoting ammonia volatilisation [29]. Biological nitrification is unlikely in aerobic pond; however, $\text{NH}_3\text{-N}$ removed by gaseous ammonia stripping or its assimilation in algal biomass can occur in anaerobic pond. Orthophosphate can be released from solids into dissolved form during anaerobic treatment of the dairy manure. This counterbalanced the loss of some phosphate molecules through mineralisation, thus resulting in a consistent total concentration of PO_4^{3-} after anaerobic pre-treatment. On the other hand, PO_4^{3-} concentration was markedly lower in the aerobic pond. Hence, a pragmatic solution to reclaiming the phosphorus is to recover it from anaerobically treated dairy manure.

Table 1

2.3. Experimental protocol of the FO system

A lab-scale cross-flow filtration set-up with a flat sheet FO membrane (active filtration surface area of 50 cm^2) was used. A schematic diagram of the lab-scale FO system is presented in Supplementary information (Figure S1). Flat sheet thin film composite (TFC) membranes were purchased from Porifera Inc, Court Hayward, USA. This membrane is made of polyamide on polysulfone support [30]. Key properties of the TFC membrane are shown in Supplementary Information (Table S1). The FO membrane cell comprised two identical blocks (feed side and draw solution side) made of acrylic plastic. Channels of effective dimensions of 36 mm width, 167 mm length and 1.4 mm height were engraved on both sides for the feed and draw solutions.

The FO experiments were commenced with an initial feed volume of 1.5 L, and filtration was continued until a 60% water recovery was achieved. The initial draw solution volume was 1

1 L. The solutions were recirculated at 1 L/min by two gear pumps (Micropump, Washington,
2 USA) regulated by rotameters. Three draw solutes, namely, sodium chloride (NaCl),
3 ethylenediaminetetraacetic acid disodium salt (EDTA-2Na) and magnesium chloride (MgCl₂)
4 were compared in this study. Analytical grade chemicals were dissolved in DI water to
5 achieve a concentration equivalent to an osmotic pressure of 90 bar. The draw solution tank
6 was placed on a digital balance (Mettler-Toledo Inc., Hightstown, USA) to monitor the
7 weight increment of the permeate from the feed tank to determine the water permeate flux.
8 The draw solution gets diluted as clean water permeates through the membrane. A small
9 amount from a concentrated draw solution (5 M) was added to the draw solution tank to keep
10 a constant osmotic pressure. A conductivity probe (Cole-Parmer, Illinois, USA) was
11 submerged into the draw solution. This probe was linked to the concentrated draw solution-
12 dosing peristaltic pump to control the concentration of draw solution. The orientation of the
13 FO membrane for all tests was 'FO mode' i.e., active layer facing the feed solution. A 20 mL
14 sample was taken from the concentrated feedwater at 15%, 30%, 45% and 60% water
15 recovery for subsequent analysis. The reverse draw solute flux of each solute was calculated
16 by recording the conductivity changes in the feed solution (DI water) over time.
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41

42 **2.4. Phosphorus recovery protocol**

43 The concentrated feed remaining after operating the FO system for a clean water recovery of
44 60% was filtered (0.45 µm). 1 M NaOH was added to the concentrated sample to increase the
45 pH to 9.5 in order to form struvite crystals. A pH of 9.5 was selected as it could facilitate the
46 deprotonation of ammonium [5], resulting in improvement of the production of struvite. The
47 concentrated solution was mixed at laboratory temperature (22 ± 1 °C) for 30 min by a
48 magnetic stirrer at 400 rpm. After stirring, the solution was allowed to settle for 24 hrs. The
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

obtained crystals were washed with Milli-Q water and then dried in a desiccator at laboratory temperature before further analysis.

2.5. Analytical techniques

Chemical oxygen demand (COD), total nitrogen (TN), phosphate (PO_4^{3-}), ammonia-nitrogen ($\text{NH}_3\text{-N}$) and nitrate (NO_3^-) were analysed using a Hach DR3900 spectrophotometer. Electrical conductivity and pH were determined by an Orion 4-Star Plus pH/conductivity meter (Thermo Scientific, MA). Total suspended solid (TSS) concentration was determined following the Standard Methods for the Examination of Water and Wastewater.

The concentration of calcium (Ca^{2+}), magnesium (Mg^{2+}) and sodium (Na^+) was analysed by inductively coupled plasma-optical emission spectroscopy (ICP-OES 710, Agilent, Australia). Before analysis, each sample was diluted using 5% nitric acid (Suprapur, Sigma-Aldrich, Australia).

The recovered crystals were characterised using scanning electron microscopy integrated with energy dispersive spectroscopy (SEM-EDS) (JSM-6490, Tokyo, Japan). The purity of the crystals was determined using X-ray diffraction (XRD) spectra (GBC MMA, Hampshire, IL). The chemical composition of the recovered product was also analysed by dissolving 1 g of recovered sample in 100 mL of 5% HNO_3 using ICP-OES and spectrophotometer.

3. Results and Discussion

3.1. Impact of draw solutes on permeate water flux and reverse salt flux

The normalised flux versus water recovery for different draw solution is shown in Figure 1a. At 60% water recovery, a water flux decline of 82%-96% was observed due to increased

organic loading. There was a significantly lower flux decline for MgCl_2 than EDTA-2Na as draw solution. For NaCl, flux decline was most prominent (Figure 1a). The difference in water flux at the same osmotic pressure was likely due to the different levels of ICP induced by each draw solute [17, 31]. It has been reported that ICP is influenced by the kinetic characteristics of the draw solute, such as diffusivity and molecular size [17].

A baseline test was performed using DI water to assess the extent of pure water flux and reverse solute flux. As shown in Figure 1b, MgCl_2 provided a pure water flux of $21.12 \text{ L/m}^2 \text{ h}$ along with a low reverse salt flux of $7.72 \text{ g/m}^2 \text{ h}$. NaCl produced a pure water flux of $19.92 \text{ L/m}^2 \text{ h}$ which was almost similar to that for EDTA-2Na ($18.72 \text{ L/m}^2 \text{ h}$). However, the reverse solute flux was significantly higher for NaCl ($16.62 \text{ g/m}^2 \text{ h}$) than EDTA-2Na ($3.69 \text{ g/m}^2 \text{ h}$). Our data confirms more rapid back diffusion of Na^+ than EDTA through the membrane (Figure 1a). This may be attributed to the larger size and higher negative charge of EDTA [32].

The level of salt accumulation was inversely proportional to the extent of reverse solute flux selectivity (RSFS) due to the effects of ICP. Both MgCl_2 and EDTA-2Na showed a higher RSFS than NaCl as draw solute (Figure 1b) while showing lower back diffusion of bulk solute through the membrane. Both MgCl_2 and NaCl contain chloride ion, but MgCl_2 exhibited higher RSFS i.e., lower reverse solute flux because of the larger electron-proton attraction for Mg^{2+} [33].

Figure 1

3.2. Change in conductivity, pH and magnesium concentration

With progressive water recovery, salt accumulated in the concentrated feed solution, increasing the solution conductivity (Figure 2a). This affected the clean water flux adversely. The conductivity-increase was observed to vary with the draw solution used. With NaCl, the conductivity of the concentrated feedwater markedly increased as the recovery of water increased, whereas MgCl_2 and EDTA-2Na showed a noticeably lower conductivity-increase, indicating an effective mitigation of the accumulation of salinity level in the concentrated feedwater.

The pH of the wastewater gradually increased for all three draw solutions due to the diffusion of proton from the feed solution to the draw solution (Figure 2b). Diffusion of proton occurs to maintain electroneutrality of the solution due to reverse solute flux [34, 35]. For EDTA-2Na, the pH of the feed solution increased at a slower rate than that of the other two solutes. This can be attributed to the markedly lower reverse solute flux in case of EDTA-2Na.

The FO membrane also retained Mg^{2+} in the feed solution (Figure 2c). As expected, when MgCl_2 was used as the draw solution, a significantly higher Mg^{2+} level in the feedwater as compared to EDTA-2Na and NaCl was detected. This was due to feed volume reduction and diffusion of Mg^{2+} from the draw to feed solution.

Figure 2

3.3. Enhancement and rejection of contaminants under different draw solutions

The concentration of $\text{NH}_3\text{-N}$ and PO_4^{3-} , which are two critical constituents of struvite, enriched proportionally in the feedwater with the water recovery of the FO system. The FO process could concentrate nutrients and COD up to nearly 2.5-fold (Figure 3a-e). A different

1 result was reported by Ansari, Hai, Price and Nghiem [25] who found that the enhancement
2 of PO_4^{3-} reduced with the water recovery due to the removal of PO_4^{3-} . This was possibly
3 because of the higher level of feedwater pH (8.03) compared to the current study (feedwater
4 pH 6.92), resulting in calcium phosphate precipitation during the filtration process. At 60%
5 water recovery, both MgCl_2 and EDTA-2Na, compared to NaCl, exhibited slightly greater
6 concentration of the nutrients and COD in the ATDM.
7
8
9
10
11
12
13
14
15
16

17 The FO membrane could reject 97%-99% of COD in the feed solution. The rejection of
18 nitrogenous compounds was variable. There was 70%-73% rejection of $\text{NH}_3\text{-N}$. The low
19 rejection of $\text{NH}_3\text{-N}$ was due to the bidirectional diffusion of cations through the TFC
20 membrane [36]. $\text{NH}_3\text{-N}$ readily diffuses through the TFC membrane from the feed to the
21 draw solution. This is likely due to its high electrostatic attraction to the negatively charged
22 polyamide surface [36]. Increased pH of the ATDM after FO-concentration also increased the
23 equilibrium ratio of $\text{NH}_3/\text{NH}_4^+$ (ammonium) pair, and thus influenced the low $\text{NH}_3\text{-N}$
24 rejection by the TFC membrane [37]. A high rejection of NO_3^- (78%-84%) was obtained;
25 however, this high rejection did not affect the FO performance for TN rejection (73%-76%).
26 This is because the concentration of NO_3^- was small in the FO feed solution. It is noted that
27 the draw solution type had little impact on the retention of the aforementioned contaminants
28 by the FO membrane.
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48

49 There was more than 98% of PO_4^{3-} rejection at 60% water recovery by the FO membrane for
50 all draw solutions. A similarly high rejection efficiency of PO_4^{3-} was reported by Wang,
51 Zheng, Tang, Wang and Wu [38] for municipal wastewater and by Zhang, She, Chang, Tang
52 and Webster [24] for urine. Both steric hindrance and electrostatic repulsion play a role here
53 [22]. Notably, the difference in rejection of PO_4^{3-} and $\text{NH}_3\text{-N}$ by FO was due to the effect of
54
55
56
57
58
59
60
61
62
63
64
65

hydrated radius of these ions [39]. According to Kiriukhin and Collins [40], compared to NH_4^+ , PO_4^{3-} has a larger hydrated radius (0.339 nm vs. 0.104 nm) and a smaller diffusion coefficient ($0.44 \times 10^{-9} \text{ m}^2/\text{s}$ vs $1.96 \times 10^{-9} \text{ m}^2/\text{s}$), which can explain the greater rejection of PO_4^{3-} by the FO membrane (Figure 3).

Figure 3

3.4. Phosphorus recovery as struvite using chemical precipitation

The increased pH and the enrichment of PO_4^{3-} , $\text{NH}_3\text{-N}$ and Mg^{2+} in the feed solution following FO operation provide favourable conditions for struvite precipitation by improving the precipitation kinetics. The precipitated solids were analysed to identify the crystal structure, morphology and element composition. The SEM image revealed that the precipitated crystals were of a typical orthorhombic structure (Figure 4a), which is similar to the pure struvite crystal standard. EDS analysis of the recovered solids confirmed that the materials contain P and Mg which are also the major elements of struvite crystal. EDS did not detect nitrogen as it is a ‘light’ element i.e., possesses low atomic number. The peak intensity of P and Mg in the EDS spectrum was higher for the MgCl_2 draw solution than the EDTA-2Na or NaCl draw solutions. However, as shown by the EDS spectra of two sites on the crystal, the elements were homogeneously distributed (Figure 4b).

Figure 4

The peak intensity of the elements for the MgCl_2 draw solution was closer to that of the struvite standard compared to the EDTA-2Na and NaCl draw solutions (Figure 5a). When MgCl_2 was used as the draw solution in the FO process, the reverse Mg^{2+} diffusion substantially enhanced the Mg^{2+} level in the feed water, thereby augmenting the Mg^{2+} level

for struvite formation. For MgCl_2 , XRD analysis of the precipitated crystals showed several peaks between 20° and 40° (2-theta degree) with well-detected intensities. Chemical analysis using ICP-OES and colorimetric measurements of the recovered struvite dissolved in nitric acid showed that the recovered product composition was 7%-9% phosphorus, 3%-5% nitrogen, and 5%-11% magnesium (Figure 5b). This shows that the components are present in a comparable ratio as in the pure struvite (12.6% phosphate, 5.7% nitrogen, and 9.9% magnesium).

Figure 5

3.5. Implications

Resource recovery from dairy manure presents a potentially renewable source of nutrients. Approximately 15%-20% of the world's phosphorus demand could be achieved by recovering phosphorus from wastewater streams [41]. The concept of using FO membranes to concentrate the wastewater to facilitate struvite recovery from dairy manure can be utilised for phosphate fertiliser production. According to our study, compared to NaCl and EDTA-2Na , MgCl_2 could achieve a better water flux and concentrated feed solution with lower salinity but without losing the available PO_4^{3-} , $\text{NH}_3\text{-N}$ and Mg^{2+} . Since a high water flux along with low reverse solute flux is a major requirement for the FO technology for reducing replenishment costs and salinity build-up, MgCl_2 can be recommended for phosphorus recovery from ATDM. However, the comparably higher cost of the magnesium salts [42] may be a potential barrier for the scale-up of this process. A comprehensive cost comparison would be helpful, but that is beyond the scope of this study.

In the FO process, water drawn from the feed side goes to a highly saline draw solution. Since FO itself does not produce fresh water, the management of the diluted draw solution is

a challenge for the widespread application of the FO process. Hence, a subsequent water recovery and draw solution regeneration process needs to be used. A study note that draw solution recovery using chemical precipitation may be less attractive on large-scale because it not only requires additional chemicals but may also generate more by-products [43]. However, a large number of studies have reported that freshwater can be effectively produced from the diluted draw solution by combining a nanofiltration (NF) [44], or reverse osmosis (RO) [45], or membrane distillation (MD) [21] system with the FO process. These processes could produce clean water and generate re-concentrated draw solution which can be used as a fresh draw solution for FO operation. Studies also noted that the energy consumption of 1 m³ fresh water produced by RO is still up to 1.5-2.5 kWh, which is 5~10 times lower than that of thermal distillation [46]. Yangali et al. [47] used low-pressure RO for draw solution recovery and they noted that this hybrid FO-RO system could save 50% of energy consumption (~1.5 kWh/m³) compared with stand-alone RO system (2.5~4 kWh/m³). Unlike RO or NF, MD can use thermal energy directly. The potential of using waste-heat or solar thermal energy makes MD specially attractive. Since MD can achieve complete rejection of nonvolatile solutes [48, 49], it is an effective process for the recovery of fresh water and re-concentration of draw solution [50, 51]. Some studies have already demonstrated the effectiveness of MD when combined with FO for draw solution regeneration [52, 53].

4. Conclusions

The present study compared the performance of three draw solutions to concentrate phosphorous from anaerobically treated dairy manure (ATDM) via FO process and subsequently recover it as struvite crystals. The FO membrane was able to effectively reject PO₄³⁻ and Mg²⁺ and contribute to their enrichment in ATDM. The FO system obtained a PO₄³⁻ concentration factor of 2.5 at a water recovery rate of 60%. Both MgCl₂ and EDTA-

2Na as draw solutes were more efficient than NaCl in reducing the level of salinity build-up in the concentrated ATDM. This was attributed to their lower reverse solute fluxes. MgCl₂ enhanced the pre-concentration of dairy manure for struvite precipitation more effectively than the other draw solutes. This is because the elevated pH and higher Mg²⁺ concentrations achieved in case of MgCl₂ enabled bi-directional transport of protons from the dairy manure and thus enhanced the struvite precipitation kinetics. Notably, supersaturation of various chemical species close to the membrane surface may lead to their precipitation onto the membrane surface, causing membrane fouling. It is recommended that the future studies address this issue, but this is beyond the scope of the current study. Moreover, the applicability of these processes needs to be systematically evaluated at pilot- and full-scales along with an economic evaluation.

Acknowledgements

A Vice-Chancellor's Postdoctoral Research Fellowship to Dr Biplob Kumar Pramanik by the University of Wollongong, Australia is gratefully acknowledged.

References

- [1] S.O. Petersen, S. Sommer, F. Béline, C. Burton, J. Dach, J. Dourmad, A. Leip, T. Misselbrook, F. Nicholson, H.D. Poulsen, *Livestock Science*, 112 (2007) 180-191.
- [2] Y. Liu, J.-H. Kwag, J.-H. Kim, C. Ra, *Desalination*, 277 (2011) 364-369.
- [3] L. Wang, Y. Li, P. Chen, M. Min, Y. Chen, J. Zhu, R.R. Ruan, *Bioresource Technology*, 101 (2010) 2623-2628.
- [4] A.C. Wilkie, W.W. Mulbry, *Bioresource Technology*, 84 (2002) 81-91.
- [5] N. Morales, M.A. Boehler, S. Buettner, C. Liebi, H. Siegrist, *Water*, 5 (2013) 1262-1278.
- [6] K. Suzuki, Y. Tanaka, K. Kuroda, D. Hanajima, Y. Fukumoto, T. Yasuda, M. Waki, *Bioresource Technology*, 98 (2007) 1573-1578.
- [7] O. Ichihashi, K. Hirooka, *Bioresource Technology*, 114 (2012) 303-307.
- [8] A. Britton, F.A. Koch, D.S. Mavinic, A. Adnan, W.K. Oldham, B. Udala, *Journal of Environmental Engineering and Science*, 4 (2005) 265-277.
- [9] M. Gerardo, M. Zacharof, R. Lovitt, *Water Research*, 47 (2013) 4833-4842.
- [10] L.D. Xavier, M.C. Cammarota, L. Yokoyama, I. Volschan, *Water Science and Technology*, 69 (2014) 1546-1551.
- [11] A. Triger, J.-S. Pic, C. Cabassud, *Water Research*, 46 (2012) 6084-6094.

- [12] V. Oliveira, L.M. Ottosen, J. Labrincha, C. Dias-Ferreira, Waste and Biomass Valorization, 7 (2016) 861-869.
- [13] G. Barnett, Bioresource Technology, 49 (1994) 139-147.
- [14] K. Güngör, K. Karthikeyan, Bioresource Technology, 99 (2008) 425-436.
- [15] T. Zhang, K.E. Bowers, J.H. Harrison, S. Chen, Water Environment Research, 82 (2010) 34-42.
- [16] A.J. Ansari, F.I. Hai, W.E. Price, J.E. Drewes, L.D. Nghiem, Journal of Membrane Science, 529 (2017) 195-206.
- [17] J.R. McCutcheon, M. Elimelech, Journal of Membrane Science, 284 (2006) 237-247.
- [18] K. Luttmiah, A. Verliefde, K. Roest, L.C. Rietveld, E.R. Cornelissen, Water Research, 58 (2014) 179-197.
- [19] T.-S. Chung, S. Zhang, K.Y. Wang, J. Su, M.M. Ling, Desalination, 287 (2012) 78-81.
- [20] B.K. Pramanik, F.I. Hai, F.A. Roddick, Separation and Purification Technology, 217 (2019) 215-220.
- [21] M. Xie, L.D. Nghiem, W.E. Price, M. Elimelech, Environmental Science & Technology Letters, 1 (2014) 191-195.
- [22] W. Xue, T. Tobino, F. Nakajima, K. Yamamoto, Water Research, 69 (2015) 120-130.
- [23] W. Luo, F.I. Hai, W.E. Price, W. Guo, H.H. Ngo, K. Yamamoto, L.D. Nghiem, Bioresource Technology, 200 (2016) 297-304.
- [24] J. Zhang, Q. She, V.W. Chang, C.Y. Tang, R.D. Webster, Environmental Science and Technology, 48 (2014) 3386-3394.
- [25] A.J. Ansari, F.I. Hai, W.E. Price, L.D. Nghiem, Separation and Purification Technology, 163 (2016) 1-7.
- [26] J. Minier-Matar, A. Santos, A. Hussain, A. Janson, R. Wang, A.G. Fane, S. Adham, Environmental Science & Technology, 50 (2016) 6044-6052.
- [27] R. Longhurst, A. Roberts, M. O'Connor, New Zealand Journal of Agricultural Research, 43 (2000) 7-14.
- [28] G. Ward, J. Jacobs, in Effectiveness of dairy first pond sludge as a nutrient source for forage crop production, Australian Society of Agronomy, Adelaide (2006).
- [29] J. Fyfe, D. Hagare, M. Sivakumar, Journal of Environmental Management, 180 (2016) 133-146.
- [30] N.Y. Yip, A. Tiraferri, W.A. Phillip, J.D. Schiffman, M. Elimelech, Environmental Science & Technology, 44 (2010) 3812-3818.
- [31] Y. Xu, X. Peng, C.Y. Tang, Q.S. Fu, S. Nie, Journal of Membrane Science, 348 (2010) 298-309.
- [32] K. Luttmiah, J.W. Post, L.C. Rietveld, E.R. Cornelissen, Water Science & Technology, 70 (2014) 1677-1682.
- [33] Y.-L. Ji, B.-X. Gu, Q.-F. An, C.-J. Gao, Polymers, 9 (2017) 715.
- [34] J.T. Arena, S.S. Manickam, K.K. Reimund, B.D. Freeman, J.R. McCutcheon, Desalination, 343 (2014) 8-16.
- [35] Q. She, X. Jin, Q. Li, C.Y. Tang, Water Research, 46 (2012) 2478-2486.
- [36] X. Lu, C. Boo, J. Ma, M. Elimelech, Environmental Science & Technology, 48 (2014) 14369-14376.
- [37] J.-J. Qin, M.H. Oo, M.N. Wai, F.-S. Wong, Journal of Membrane Science, 217 (2003) 261-268.
- [38] Z. Wang, J. Zheng, J. Tang, X. Wang, Z. Wu, Scientific reports, 6 (2016) 21653.
- [39] N.T. Hau, S.-S. Chen, N.C. Nguyen, K.Z. Huang, H.H. Ngo, W. Guo, Journal of Membrane Science, 455 (2014) 305-311.
- [40] M.Y. Kiriukhin, K.D. Collins, Biophysical Chemistry, 99 (2002) 155-168.
- [41] Z. Yuan, S. Pratt, D.J. Batstone, Current opinion in biotechnology, 23 (2012) 878-883.
- [42] Z. Bradford-Hartke, J. Lane, P. Lant, G. Leslie, Environmental Science & Technology, 49 (2015) 8611-8622.
- [43] Q. Long, Y. Jia, J. Li, J. Yang, F. Liu, J. Zheng, B.J.P. Yu, 6 (2018) 165.
- [44] P. Pal, P. Das, S. Chakraborty, R. Thakura, Environmental Science and Pollution Research, 23 (2016) 21604-21618.

- [45] R. Thiruvengkatachari, M. Francis, M. Cunningham, S. Su, Separation and Purification Technology, 163 (2016) 181-188.
- [46] Q. Ge, M. Ling, T.-S. Chung, J Journal of Membrane Science, 442 (2013) 225-237.
- [47] V. Yangali-Quintanilla, Z. Li, R. Valladares, Q. Li, G.J.D. Amy, 280 (2011) 160-166.
- [48] S. Adham, A. Hussain, J.M. Matar, R. Does, A.J.D. Janson, 314 (2013) 101-108.
- [49] M. El-Bourawi, Z. Ding, R. Ma, M.J.J.o.m.s. Khayet, 285 (2006) 4-29.
- [50] S.K. Yen, M. Su, K.Y. Wang, T.-S.J.J.o.M.S. Chung, 364 (2010) 242-252.
- [51] D. Zhao, S. Chen, P. Wang, Q. Zhao, X.J.I. Lu, E.C. Research, 53 (2014) 16170-16175.
- [52] S. Zhang, P. Wang, X. Fu, T.-S.J.w.r. Chung, 52 (2014) 112-121.
- [53] M. Xie, L.D. Nghiem, W.E. Price, M. Elimelech, Environmental Science & Technology, 47 (2013) 13486-13493.

List of Figure Captions

Figure 1: (a) Impact of draw solutes on normalized flux during filtration of ATDM, (b) average water flux and reverse solute flux of MgCl_2 , NaCl , and EDTA-2Na draw solution at 90 bar osmotic pressure where feed solution was DI water. RSFS denotes the volume of permeate water per gram of solute that has diffused from the draw solution to the feed solution.

Figure 2: Variation of feedwater (a) conductivity, (b) pH and (c) Mg^{2+} concentration during anaerobically treated dairy manure pre-concentration for NaCl , MgCl_2 , and EDTA-2Na draw solution (values indicate average $\pm$ standard deviation of duplicate samples).

Figure 3: Variation of concentration and rejection of (a) COD, (b) $\text{NH}_3\text{-N}$, (c) NO_3^- , (d) TN, and (e) PO_4^{3-} during pre-concentration of anaerobically treated dairy manure at different water recovery (values indicate average $\pm$ standard deviation of duplicate samples).

Figure 4: (a) Image produced by scanning electron microscopy, (b) energy dispersive X-ray spectrometry spectra of the recovered solids for different draw solutions

Figure 5: (a) Purity of struvite crystal analysis for different draw solutions using XRD analysis, and (b) elementary composition of recovered crystals analysis using ICP-OES for Mg^{2+} and Hach spectrophotometer for PO_4^{3-} and $\text{NH}_3\text{-N}$ (data points are average values of duplicate samples).

Figure 1

Figure 2

Figure 3

Figure 4

Figure 5

Supplementary Information

Figure S1: A schematic diagram of the lab-scale FO system

Table S1: Properties of the TFC membrane (Zheng et al., 2018)

Properties	Value
Pore radius (nm)	0.37 ± 0.04
Water permeability coefficient (L/m ² h.bar)	3.2 ± 0.22
Salt (NaCl) permeability coefficient (L/m ² h)	0.41 ± 0.01
Membrane structure parameter (mm)	0.46 ± 0.05
Zeta potential (mV)	-16.2
Contact angle (active layer) (°)	49.5 ± 3.4

Zheng, L., Price, W.E., Nghiem, L.D. 2018. Effects of fouling on separation performance by forward osmosis: the role of specific organic foulants. *Environmental Science and Pollution Research*, 1-12.

Graphical Abstract

Table 1: Characteristics of the dairy manure before and after treatments (values indicate average $\pm$ standard deviation of duplicate samples)

Parameter	Raw wastewater	Anaerobic pond effluent	Aerobic pond effluent
COD (mg/L)	1240 $\pm$ 88	475 $\pm$ 24	306 $\pm$ 18
NH ₃ -N (mg/L)	176 $\pm$ 12	128 $\pm$ 11	88 $\pm$ 6
NO ₃ ⁻ (mg/L)	26 $\pm$ 3	18 $\pm$ 2	16 $\pm$ 4
TN (mg/L)	212 $\pm$ 24	154 $\pm$ 18	116 $\pm$ 16
PO ₄ ³⁻ (mg/L)	112 $\pm$ 8	109 $\pm$ 8	78 $\pm$ 6
pH	6.76 $\pm$ 0.02	6.92 $\pm$ 0.02	7.18 $\pm$ 0.03
TSS (mg/L)	2476 $\pm$ 312	516 $\pm$ 128	346 $\pm$ 96
EC (mS/cm)	4.58 $\pm$ 0.24	4.36 $\pm$ 0.12	4.12 $\pm$ 0.16
DO (mg/L)	2.32 $\pm$ 0.12	-	1.04 $\pm$ 0.10
Mg ²⁺ (mg/L)	62 $\pm$ 3	82 $\pm$ 3	74 $\pm$ 3
Ca ²⁺ (mg/L)	56 $\pm$ 3	68 $\pm$ 4	62 $\pm$ 5
Na ⁺ (mg/L)	152 $\pm$ 10	146 $\pm$ 6	158 $\pm$ 12