University of Wollongong

Research Online

Faculty of Engineering and Information
Sciences - Papers: Part A

Faculty of Engineering and Information
Sciences

1-1-2016

Occurrence of trace organic contaminants in wastewater sludge and their removals by anaerobic digestion

Shufan Yang

University of Wollongong, sy527@uowmail.edu.au

Faisal I. Hai

University of Wollongong, faisal@uow.edu.au

William E. Price

University of Wollongong, wprice@uow.edu.au

James McDonald

University of New South Wales

Stuart J. Khan

University of New South Wales, s.khan@unsw.edu.au

See next page for additional authors

Follow this and additional works at: <https://ro.uow.edu.au/eispapers>

Part of the [Engineering Commons](#), and the [Science and Technology Studies Commons](#)

Research Online is the open access institutional repository for the University of Wollongong. For further information contact the UOW Library: research-pubs@uow.edu.au

Occurrence of trace organic contaminants in wastewater sludge and their removals by anaerobic digestion

Abstract

This study aims to evaluate the occurrence of trace organic contaminants (TrOCs) in wastewater sludge and their removal during anaerobic digestion. The significant occurrence of 18 TrOCs in primary sludge was observed. These TrOCs occurred predominantly in the solid phase. Some of these TrOCs (e.g. paracetamol, caffeine, ibuprofen and triclosan) were also found at high concentrations (>10,000. ng/L) in the aqueous phase. The overall removal of TrOCs (from both the aqueous and solid phase) by anaerobic digestion was governed by their molecular structure (e.g. the presence/absence of electron withdrawing/donating functional groups). While an increase in sludge retention time (SRT) of the digester resulted in a small but clearly discernible increase in basic biological performance (e.g. volatile solids removal and biogas production), the impact of SRT on TrOC removal was negligible. The lack of SRT influence on TrOC removal suggests that TrOCs were not the main substrate for anaerobic digestion.

Disciplines

Engineering | Science and Technology Studies

Publication Details

Yang, S., Hai, F. I., Price, W. E., McDonald, J., Khan, S. J. & Nghiem, L. D. (2016). Occurrence of trace organic contaminants in wastewater sludge and their removals by anaerobic digestion. *Bioresource Technology*, 210 153-159.

Authors

Shufan Yang, Faisal I. Hai, William E. Price, James McDonald, Stuart J. Khan, and Long D. Nghiem

**Occurrence of trace organic contaminants in wastewater sludge and their
removals by anaerobic digestion**

Submitted to Bioresource Technology

November 2015

Shufan Yang ^a, James McDonald ^c, Faisal I. Hai ^a, William E. Price ^b, Stuart J. Khan ^c, Long
D. Nghiem ^{a*}

^a Strategic Water Infrastructure Lab, School of Civil, Mining and Environmental Engineering,
University of Wollongong, Australia

^b Strategic Water Infrastructure Lab, School of Chemistry, University of Wollongong
Australia

^c School of Civil and Environmental Engineering, University of New South Wales, NSW
2052, Australia

* Corresponding author. Tel: 61 2 4221 4590, Email: longn@uow.edu.au

Abstract

This study aims to evaluate the occurrence of trace organic contaminants (TrOCs) in wastewater sludge and their removal during anaerobic digestion. The significant occurrence of 18 TrOCs in primary sludge was observed. These TrOCs occurred predominantly in the solid phase. Some of these TrOCs (e.g. paracetamol, caffeine, ibuprofen and triclosan) were also found at very high concentration ($>10,000$ ng/L) in the aqueous phase. The overall removal of TrOCs (from both the aqueous and solid phase) by anaerobic digestion was governed by their molecular structure (e.g. the presence/absence of electron withdrawing/donating functional groups). While an increase in sludge retention time (SRT) of the digester resulted in a small but clearly discernible increase in basic biological performance (e.g. volatile solids removal and biogas production), the impact of SRT on TrOC removal was negligible. The lack of SRT influence on TrOC removal suggests that TrOCs were not the main substrate for anaerobic digestion.

Keyword: Anaerobic digestion, primary sludge, sludge retention time (SRT), trace organic contaminants, molecular structure.

1 Introduction

Wastewater treatment involves the settling of solid materials and transformation of dissolved and suspended organic matter to sludge. During wastewater treatment, a large volume of sludge is produced. The EU generates about 10 million tonnes of dry sludge each year (Fytli & Zabaniotou, 2008). In Australia, dry sludge production from wastewater treatment increased by about 3% each year from 0.3 million tonnes in 2010 to 0.33 million tonnes in 2013 (Semblante et al., 2014). Thus, the production of excess sludge from wastewater treatment is a vexing problem and necessitates effective management strategies.

Wastewater sludge has a high organic content and a host of pathogenic vectors. As a result, wastewater sludge must be treated or stabilised prior to environmental disposal. The organic content in wastewater sludge can be converted into energy through a range of technologies including anaerobic digestion (Karthikeyan & Visvanathan, 2013) and microbial fuel cell (Oh et al., 2014). Amongst them, anaerobic digestion is probably the most widely used technology for wastewater sludge treatment (Chernicharo et al., 2015; Kim et al., 2011).

During the anaerobic digestion process, a consortium of microbes metabolizes and converts organic substances into biogas in the absence of oxygen. Anaerobic digestion can achieve a sludge solid reduction of 40 to 60% (Malina & Pohland, 1992) and generate methane gas as a renewable fuel. The digested sludge from anaerobic digestion can be used as fertilizers and soil conditioners in agriculture (Elliott et al., 1990).

Application of the digested sludge on the land is a sustainable option because it enables the recovery of important nutrients and adds economic value to what is conventionally perceived as waste. Nevertheless, recent discovery of the widespread occurrence of trace organic contaminants (TrOCs) in municipal wastewater suggests that some of these compounds can be transferred to sludge during wastewater treatment (Citulski & Farahbakhsh, 2010; Semblante et al., 2015). These TrOCs include pesticides, industrial chemicals, components of consumer products, pharmaceuticals and personal care products, hormones, and other organic pollutants that are regularly released into municipal wastewater by anthropogenic activities (Luo et al., 2014).

TrOCs have been commonly found in municipal wastewater at very low concentrations (Verlicchi & Zambello, 2015). At a sufficient concentration, some of these TrOCs have the potential to cause chronic disorders in animals and humans. Several countries have already imposed controls on certain TrOCs such as nonylphenol and nonylphenol ethoxylates, polychlorinated biphenyls, polychlorinated dibenzo-p-dioxins and dibenzo-p-furans. However, a clear approach to address TrOCs in digested sludge has not yet been developed (Smith, 2009).

Some TrOCs are lipophilic. In other words, they can be transferred to the solid phase during primary and secondary clarification (Clarke & Smith, 2011), resulting in significantly higher concentrations (several $\mu\text{g/kg}$ dry weight or more) in sludge than wastewater. Persistent TrOCs have the potential to bioaccumulate during land application and, if left unchecked, may impose adverse risk to humans and the ecosystem.

Antibiotics and other pharmaceutically active compounds were amongst the most investigated TrOCs in digested sludge. Trimethoprim, sulfamethoxazole, ciprofloxacin and doxycycline were notable antibiotics detected at the low mg/kg dry weight range in digested sludge from Swedish wastewater treatment plants (Golet et al., 2003; Lindberg et al., 2005). Ciprofloxacin and diphenhydramine were also detected in more than 80 sludge samples across the USA (Grumbles, 2009). In Japan, Narumiya et al. (2013) reported the occurrence of 45 TrOCs in the digested sludge. Concentrations of several compounds (e.g. ofloxacin, triclosan and triclocarban) exceeded 1 mg/kg dry sludge (Narumiya et al., 2013). Several personal care products including triclosan and triclocarban have also been reported to accumulate in anaerobically digested sludge to a high concentration (Heidler & Halden, 2007; Heidler et al., 2006).

Most previous studies concerning anaerobic treatment have focused specifically on the removal of TrOC from the aqueous (water) phase. Thus, findings from these studies are not

readily applicable to anaerobic digestion of wastewater sludge. Indeed, results from recent studies (Carballa et al., 2007; Hernandez-Raquet et al., 2007; Malmborg & Magner, 2015; Narumiya et al., 2013) examining the removal of TrOCs from both aqueous and solid phases by anaerobic digestion show that the overall removal efficiency could be lower compared to studies that only reported TrOC removal from the aqueous phase.

It is noteworthy that most previous studies involved the spiking (artificial addition) of TrOCs to the feed sludge at elevated concentrations. Malmborg and Magner (2015) studied the fate of 14 different TrOCs during the anaerobic digestion by spiking each compound at 50 mg/L into the sludge. They showed that several compounds (e.g. trimethoprim, citalopram, and furosemide) were well removed by anaerobic digestion. However, several others including fluoxetine and carbamazepine were persistent to anaerobic digestion. Similar results were reported by Carballa et al. (2007) who added TrOCs to feed sludge at concentrations between 4 and 400 µg/L. Narumiya et al. (2013) was probably the only group of authors who have monitored the environmental concentrations of TrOCs in the feed sludge. Narumiya et al. (2013) showed that 4 out of 26 compounds, namely, sulfamethoxazole, trimethoprim, caffeine and acetaminophen detected in the thickened sludge were well removed by anaerobic digestion while most of the remaining compounds were not significantly removed.

This study aims to reveal the occurrence and fate of TrOCs during anaerobic digestion of primary sludge. Basic biological performance of anaerobic digesters at a range of sludge retentiontime (SRT) is systematically examined. TrOCs concentrations in the aqueous and solid phase from both primary and digested sludge are quantified to examine their fate during anaerobic digestion.

2 Materials and Methods

2.1 Wastewater sludge

Anaerobically digested sludge and primary sludge were taken from a full scale wastewater treatment plant in New South Wales (Australia) as inoculum and feed, respectively. The primary sludge was stored at 4 °C for a maximum of 2 weeks before fresh sludge was collected again. The total solids (TS) content of this primary sludge was 25.7±6.6 g/L (average ± standard deviation of eight samples). The ratio of volatile solids (VS) over TS (VS/TS) of this primary sludge was stable (0.89±0.03) during the current study. pH value of the primary sludge was in the range of 5.35 to 5.59.

2.2 Anaerobic digester

Three identical anaerobic digesters were used. Each digester (Supplementary Data Figure S1) consists of a 28 L conical shape stainless steel reactor, a peristaltic hose pump (DULCO® Flex from ProMinent Fluid Controls, Australia), a thermal couple with temperature gauge, a custom made gas counter, and a gas trap for biogas sampling. Hot water flowing inside a rubber hose wrapping around the digester was used for heating. The entire reactor was insulated by polystyrene foam. The temperature of the digester was maintained at 35.0 ± 0.5 °C by regulating the temperature inside the rubber hose using a temperature control unit (Neslab RTE 7, Thermo Fisher Scientific, Newington, USA). When necessary, biogas from the gas counter can be directed to a gas trap for biogas composition analysis.

2.3 Experimental protocol

Each digester was seeded with anaerobically digested sludge at the beginning of the experiment. The peristaltic pump was operated continuously at the flow rate of 60 L/h to provide sufficient sludge mixing. The active volumes of all three digesters were maintained at 20 L throughout the experiment. The SRT of the three digesters were set at 15, 20 and 30 d, respectively, by withdrawing and feeding a predetermined volume of sludge each day. The digesters were first stabilized for two weeks. Digested sludge and feed samples were then collected for analysis over 12 weeks of continuous operation.

2.4 Analytical methods

2.4.1 Biogas production and composition

Biogas production was monitored using an online gas counter. Biogas composition analysis was conducted every week. Approximately 1 L of biogas was collected in the gas trap (Supplementary Data Figure S1). A portable gas analyser (GA5000 gas analyser, Geotechnical Instruments (UK) Ltd, England) was then used for biogas composition analysis (Nghiem et al., 2014). Methane production activity ($\text{L-CH}_4/\text{g VS}_{\text{removed}}$) was calculated based on the methane composition in biogas and the biogas production rate.

2.4.2 Sludge characteristics

Sludge samples were taken weekly from each digesters as well as primary sludge. The tested sludge characterization parameters included TS, VS, total chemical oxygen demand (tCOD), soluble chemical oxygen demand (sCOD), pH, and alkalinity. The pH of the sludge samples was measured by a pH meter (Orion 4 Star pH and conductivity portable meter, Thermo Scientific, Australia). TS, VS, and alkalinity were measured in accordance to the standard methods (Eaton et al., 2005). COD was measured following the US-EPA Method 8000 using high range COD vials (HACH, USA). The supernatant used for measurement of sCOD was

obtained by centrifuging sludge sample at 3720xg for 10 minutes (Allegra X-12R centrifuge, Beckman Coulter, Australia), and then filtering through 1 µm glass microfiber filter paper (Filtech, Australia).

2.4.3 TrOC sample preparation and analysis

Duplicated TrOCs samples were taken from digested sludge and primary sludge approximately every 7 days. The concentration of TrOCs in the sludge phase was determined according to a method previously described by Wijekoon et al. (2014). Briefly, analytes were separated using an Agilent (Palo Alto, CA, USA) 1200 series high performance liquid chromatography (HPLC) system on a Luna C18 (2) column (Phenomenex, Torrance CA, USA). Peaks were identified and quantified by mass spectrometry using an API 4000 triple quadrupole mass spectrometer (Applied Biosystems, Foster City, CA, USA) equipped with a turbo-V ion source employed in both positive and negative electro-spray modes. The limit of quantification of this analytical technique was 20 ng/L for bisphenol A, 10 ng/L for caffeine, triclocarban, and diuron, and 5 ng/L for all other compounds reported in this study.

Sludge samples were centrifuged at 3720xg for 10 minutes (Allegra X-12R, Beckman Coulter, USA) to obtain solid pellets and supernatant for further analysis. Supernatant (50 mL) from the sludge sample was diluted to 500 mL by Milli-Q water, and filtered by 1 µm and 0.7 µm pore size glass microfiber filter paper for solid phase extraction (SPE). The pellets from the sludge sample were freeze-dried for 10 h using the Alpha 1-2 LDplus Freeze Dryer (Christ GmbH, Germany). The dried sample was then grounded to powder and 0.5 g powder was transferred to a 13 mL glass vial (with cap) for extraction. Methanol (10 mL) was added to the vial, mixed thoroughly by vortex mixer (VM1, Ratek, Australia), and ultrasonicated for 10 minutes at 40 °C. The sample was centrifuged at 3720xg for 10 minutes, and the supernatant was collected. A solvent made of dichloromethane and methanol (1:1, v/v) (10 mL) was added to the remaining sludge, and supernatant was collected by following the previous processes. The supernatant from both steps were combined, diluted into 500 mL by Milli-Q water, and filtered by 1 µm and then 0.7 µm pore size glass microfiber filter paper for subsequent SPE.

The extracted liquid samples from both the sludge supernatant and solid were spiked with surrogate (50 µL per sample) containing 36 isotopically labelled standards (Supplementary Data Table S2) for method recovery and detection level determination. The liquid samples were then loaded onto the HLB cartridges conditioned with 5 mL methyl tert-butyl ether, 5 mL methanol, and 2 x 5 mL Milli-Q water at the flow rate of approximately 15 mL/min. After

concentrating to 1 mL, eluted samples were subjected to gas chromatography tandem mass spectrometry (GC–MS/MS) analysis (McDonald et al., 2012).

2.4.4 TrOC mass balance

The inlet TrOC concentration can be denoted as:

$$C_{in} = X_{in} \times TS_{in} + S_{in} \quad (1)$$

where C_{in} is the total inlet concentration (ng/L), X_{in} is the TrOC concentration in the solid phase of primary sludge (ng/g dry sludge), TS_{in} is the total solid concentration of primary sludge (g/L), and S_{in} is the TrOC concentration in the aqueous phase of primary sludge (ng/L). Similarly in the outlet sludge, the concentration of TrOC can be calculated as

$$C_{out} = X_{out} \times TS_{out} + S_{out} \quad (2)$$

where C_{out} is the total outlet concentration (ng/L), X_{out} is the TrOC concentration in the solid phase of digested sludge (ng/g dry sludge), TS_{out} is the total solid concentration of digested sludge (g/L) and S_{in} is the TrOC concentration in the aqueous phase of digested sludge (ng/L). Thus the mass balance for TrOC concentration can be presented as

$$C_{in} = C_{out} + C_{bio} \quad (3)$$

where C_{bio} is the portion of TrOC that has been biodegraded.

3 Results and discussion

3.1 Anaerobic digester performance

Biogas production rate and composition are key parameters to examine the anaerobic digester performance. As the SRT was increased from 15 to 30 d, a notable increase in methane production activity from 0.23 to 0.69 L-CH₄/g VS_{removed} could be observed (Figure 1). On the other hand, biogas composition was not affected by the digester SRT. Indeed, all biogas samples were composed of approximately 60% methane and 40% carbon dioxide regardless of the digester SRT.

[FIGURE 1]

Corresponding to the observed increase in methane production activity due to increasing SRT, a small nevertheless discernible improvement in the reduction of both TS and VS can be observed (Table 1). As expected, the reduction of VS was consistently higher than that of TS. As the SRT increased from 15 to 30 days, VS reduction increased from 69.3 to 75.8%. A similar observation could be made regarding the removal of tCOD. Indeed, tCOD removal increased from roughly 70 to 77% when SRT increased from 15 to 30 d (Table 1). On the

other hand, the removal of sCOD was not significantly affected by SRT. It should be noted that the soluble COD fraction was relatively small (approximately 2,000 mg/L) compared to the total COD content of the feed (approximately 35,000 mg/L). Overall, results presented in Table 1 show notable improvement in basic performance parameters by increasing the SRT beyond 15 days, which can be attributed to the enhanced methanogenic population and activity at high SRT (Rubia et al., 2006).

[TABLE 1]

It is noteworthy that the alkalinity at pH=4.5 (Supplementary Data Figure S3) and pH value of each digester were also monitored throughout the experiment. The mixed liquor pH values of all three digesters were in the range typical for normal anaerobic digestion (i.e. 7.45 to 7.66). Alkalinity of all digesters was also stable, ranging from 2000 to 3800 mg CaCO₃/L. Over all, all three digesters were in good condition throughout the current study. There was no indication of volatile fatty acid or ammonia accumulation in the digesters.

3.2 TrOC occurrence in primary sludge

Of the 36 TrOCs monitored in this study (Supplementary Data Table S2), 18 compounds were consistently detected in all primary sludge samples (Table 2). Their concentrations as well as distribution between the aqueous and solid phase varied significantly. Of these TrOCs, paracetamol, caffeine, ibuprofen and triclosan showed the highest concentrations (>10,000 ng/L) in the aqueous phase. The prevalent occurrence of these TrOCs in primary sludge can be attributed to their widespread use in our modern society. Paracetamol and ibuprofen are over-the-counter analgesic and antipyretic drugs. Triclosan is an antibacterial/antifungal agent widely used in soap, detergent, and toothpaste. Caffeine is a stimulant occurring naturally in tea and coffee. Overall, their frequent use in daily life is consistent with the accumulation of these TrOCs in primary sludge (Stasinakis, 2012).

[TABLE 2]

All 18 TrOCs detectable in this study occurred predominantly in the solid phase. In all cases, their concentration in the solid phase (in ng/Kg) was much higher than that in the aqueous phase (in ng/L). pH value of the primary sludge was in the range of 5.35 to 5.59 (Section 2.1). Thus, log D value at pH 5 was used to determine the hydrophobicity of these TrOCs. The distribution of these TrOCs in the solid phase increased as their log D value increased (Table 2). For all TrOCs with moderate hydrophobicity (log D >2), 72 to 99% of the total mass partitioned in the solid phase (Table 2). In line with recent studies concerning anaerobic treatment of wastewater (Monsalvo et al., 2014; Wang et al., 2014; Wijekoon et al., 2015),

the results here indicate the need to systematically investigate the fate and transport of TrOCs in the liquid and solid phases during anaerobic digestion.

The high standard deviation shown in Table 2 also indicates a significant temporal variation in their occurrence in primary sludge. The SRT values (15 to 30 days) used in this study were comparable or significantly higher than the sampling interval (Section 2.1). Thus, some variation in the calculated removal efficiency would be expected.

3.3 The fate of TrOCs during the anaerobic digestion

Concentrations of TrOCs in the aqueous and solid phase before and after anaerobic digestion with SRT of 15, 20, and 30 days are shown in Figures 2 and 3. TrOC removals from both the aqueous and solid phase varied greatly. For example, atenolol, caffeine, trimethoprim, paracetamol and naproxen were well removed from the aqueous phase. These compounds were also effectively removed from the solid phase by anaerobic digestion. On the other hand, several TrOCs including carbamazepine, gemfibrozil, verapamil, amitriptyline, diuron, clozapine, bisphenol A, triclosan, and triclocarbon showed no or only negligible removal from either the liquid or the solid phase.

[FIGURE 2]

[FIGURE 3]

pH values of the primary sludge was from 5.35 to 5.59, while the digested sludge pH was in the range of 7.46 to 7.66. This pH increase during anaerobic digestion facilitates the transfer of some TrOCs between the aqueous and solid phase, particularly those that are ionisable with a pKa value in the vicinity of pH 5 to 7. A notable example is ibuprofen. With a pKa value of 4.9, ibuprofen can change from a moderately hydrophobic to a hydrophilic (increasing solubility in water) form. As a result, while there was a notable decrease in ibuprofen concentration in the solid phase due to anaerobic digestion, a small but discernible increase in ibuprofen concentration in the aqueous phase can be observed. To account for the possible transfer from the solid to aqueous phase, mass distribution of each TrOC between the two phases and biodegradation after anaerobic digestion under different SRT is also presented in Figure 4.

As noted above, hydrophobicity (measured by log D value) of TrOCs is a key factor governing their distribution between the solid and aqueous phase. Nevertheless, unlike several previous studies (Monsalvo et al., 2014; Tadkaew et al., 2011; Wijekoon et al., 2015) where removal from the aqueous phase was the primary concern, results in Figure 4 show that the overall TrOC removal by anaerobic digestion was not significantly influenced by their

hydrophobicity. On the other hand, the qualitative biodegradation prediction framework proposed by Tadkeaw et al. (2010) and Wijekoon et al. (2015) for aerobic and anaerobic membrane bioreactors, respectively, can be used to explain the removal data in Figure 4. TrOCs with strong electron donating functional groups were readily degradable by anaerobic digestion (Supplementary Data Table S4). Examples of these strong electron donating functional groups are provided in Supplementary Data Table S5. As a result, atenolol, caffeine, trimethoprim, paracetamol, naproxen, and amitriptyline were well removed by anaerobic digestion (Figure 4). On the other hand, TrOCs with strong electron withdrawing functional groups were resistant to anaerobic digestion (Supplementary Data Table S4). Compounds in this group include diclofenac, gemfibrozil, carbamazepine, diuron, and triclocarban given the presence of their chloro and amide moieties which are strong electron withdrawing functional groups (Supplementary Data Table S5). It is noted that no removal of bisphenol A was recorded in this study despite the presence of a strong electron donating functional group (hydroxyl). The reason for this observation cannot be confirmed but the release of bisphenol A from plastic component of the experimental system is a plausible explanation.

[FIGURE 4]

Data presented in Figures 2-4 show no or only marginal improvement in the removal of TrOCs when the SRT increased from 15 to 30 days. These results are in good agreement with a previous study by Carballa et al. (2007) who did not observe any notable increase in the removal of several hydrophilic organic compounds as the SRT value increased from 10 to 30 d. The relative independence between SRT and TrOC removal could be attributed to the fact that they are not the main substrate for the anaerobic digestion process. It is also possible that the improvement in TrOC removal with increasing SRT was not significant and was masked by the variation in feed concentration as discussed in section 3.2.

Conclusion

In this study, 18 trace organic contaminants (TrOCs) were consistently detected in all primary sludge samples. These TrOCs occurred predominantly in the solid phase. The overall removal of TrOCs (from both the aqueous and solid phase) and their fate during anaerobic digestion were governed by their molecular structure (e.g. the presence/absence of electron withdrawing or donating functional groups). An increase in sludge retention time (SRT) of the digester resulted in a small but clearly discernible increase in basic biological performance (e.g. volatile solids removal and biogas production). On the other hand, the impact of SRT on TrOC removal was negligible.

Reference

- [1] Carballa, M., Omil, F., Ternes, T., Lema, M.J. 2007. Fate of pharmaceutical and personal care products (PPCPs) during anaerobic digestion of sewage sludge. *Water Research*, 41, 2139-2150.
- [2] Chernicharo, C.A.L., van Lier, J.B., Noyola, A., Bressani Ribeiro, T. 2015. Anaerobic sewage treatment: state of the art, constraints and challenges. *Reviews in Environmental Science and Bio/Technology*, 1-31.
- [3] Citulski, J.A., Farahbakhsh, K. 2010. Fate of endocrine-active compounds during municipal biosolids treatment: A review. *Environmental Science & Technology*, 44, 8367-8376.
- [4] Clarke, O.B., Smith, R.S. 2011. Review of 'emerging' organic contaminants in biosolids and assessment of international research priorities for the agricultural use of biosolids. *Environment International*, 37, 226-247.
- [5] Eaton, D.A., Clesceri, S.L., Greenberg, E.A. 2005. *Standard Methods for Examination of Water & Wastewater* 21st ed. American Public Health Association
- [6] Elliott, A.H., Dempsey, A.B., Hamilton, W.D., DeWolfe, R.J. 1990. *Land application of water treatment sludges: impacts and management*. American Water Works Association, Denver.
- [7] Fytli, D., Zabaniotou, A. 2008. Utilization of sewage sludge in EU application of old and new methods—A review. *Renewable and Sustainable Energy Reviews*, 12, 116-140.
- [8] Golet, E.M., Xifra, I., Siegrist, H., Alder, A.C., Giger, W. 2003. Environmental exposure assessment of fluoroquinolone antibacterial agents from sewage to soil. *Environmental Science & Technology*, 37, 3243-3249.
- [9] Grumbles, B.H. 2009. Targeted national sewage sludge survey statistical analysis report. United states environmental protection agency office of water.
- [10] Heidler, J., Halden, U.R. 2007. Mass balance assessment of triclosan removal during conventional sewage treatment. *Chemosphere*, 66, 362-369.
- [11] Heidler, J., Sapkota, A., Halden, R.U. 2006. Partitioning, persistence, and accumulation in digested sludge of the topical antiseptic triclocarban during wastewater treatment. *Environmental Science & Technology*, 40, 3634-3639.

- [12] Hernandez-Raquet, G., Soef, A., Delgenès, N., Balaguer, P. 2007. Removal of the endocrine disrupter nonylphenol and its estrogenic activity in sludge treatment processes. *Water Research*, 41, 2643-2651.
- [13] Karthikeyan, O.P., Visvanathan, C. 2013. Bio-energy recovery from high-solid organic substrates by dry anaerobic bio-conversion processes: a review. *Reviews in Environmental Science and Biotechnology*, 12, 257-284.
- [14] Kim, J., Novak, T.J., Higgins, J.M. 2011. Multistaged anaerobic sludge digestion processes. *Journal of Environmental Engineering* 137, 746-753.
- [15] Lindberg, R.H., Wennberg, P., Johansson, M.I., Tysklind, M., Andersson, B.A.V. 2005. Screening of human antibiotic substances and determination of weekly mass flows in five sewage treatment plants in Sweden. *Environmental Science & Technology*, 39, 3421-3429.
- [16] Luo, Y., Guo, W., Ngo, H.H., Nghiem, L.D., Hai, F.I., Zhang, J., Liang, S., Wang, X.C. 2014. A review on the occurrence of micropollutants in the aquatic environment and their fate and removal during wastewater treatment. *Science of the total environment*, 473–474, 619-641.
- [17] Malina, F.J., Pohland, G.P. 1992. Design of anaerobic processes for the treatment of industrial and municipal wastes. Technomic publishing company, Lancaster.
- [18] Malmborg, J., Magner, J. 2015. Pharmaceutical residues in sewage sludge: Effect of sanitization and anaerobic digestion. *Journal of Environmental Management*, 153, 1-10.
- [19] McDonald, A.J., Harden, B.N., Nghiem, D.L., Khan, J.S. 2012. Analysis of N-nitrosamines in water by isotope dilution gas chromatography–electron ionisation tandem mass spectrometry. *Talanta*, 99, 146-154.
- [20] Monsalvo, V.M., McDonald, J.A., Khan, S.J., Le-Clech, P. 2014. Removal of trace organics by anaerobic membrane bioreactors. *Water Research*, 49, 103-112.
- [21] Narumiya, M., Nakada, N., Yamashita, N., Tanaka, H. 2013. Phase distribution and removal of pharmaceuticals and personal care products during anaerobic sludge digestion. *Journal of Hazardous Materials*, 260, 305-312.
- [22] Nghiem, L.D., Manassa, P., Dawson, M., Fitzgerald, S.K. 2014. Oxidation reduction potential as a parameter to regulate micro-oxygen injection into anaerobic digester for

373 reducing hydrogen sulphide concentration in biogas. *Bioresource Technology*, 173,
374 443-447.

375 [23] Oh, S.-E., Yoon, J.Y., Gurung, A., Kim, D.-J. 2014. Evaluation of electricity generation
376 from ultrasonic and heat/alkaline pretreatment of different sludge types using
377 microbial fuel cells. *Bioresource Technology*, 165, 21-26.

378 [24] Rubia, d.l.M.A., Perez, M., Romero, I.L., Sales, D. 2006. Effect of solids retention time
379 (SRT) on pilot scale anaerobic thermophilic sludge digestion. *Process Biochemistry*,
380 41, 79-86.

381 [25] Semblante, G.U., Hai, F.I., Huang, X., Ball, A.S., Price, W.E., Nghiem, L.D. 2015. Trace
382 organic contaminants in biosolids: Impact of conventional wastewater and sludge
383 processing technologies and emerging alternatives. *Journal of hazardous materials*,
384 300, 1-17.

385 [26] Semblante, G.U., Hai, F.I., Ngo, H.H., Guo, W., You, S.-J., Price, W.E., Nghiem, L.D.
386 2014. Sludge cycling between aerobic, anoxic and anaerobic regimes to reduce sludge
387 production during wastewater treatment: Performance, mechanisms, and implications.
388 *Bioresource Technology*, 155, 395-409.

389 [27] Smith, R.S. 2009. Organic contaminants in sewage sludge (biosolids) and their
390 significance for agricultural recycling. *Philosophical Transactions of the Royal*
391 *Society A: Mathematical, Physical and Engineering Sciences*, 367, 4005-4041.

392 [28] Stasinakis, S.A. 2012. Review on the fate of emerging contaminants during sludge
393 anaerobic digestion. *Bioresource Technology*, 121, 432-440.

394 [29] Tadkaew, N., Hai, F.I., McDonald, J.A., Khan, S.J., Nghiem, L.D. 2011. Removal of
395 trace organics by MBR treatment: The role of molecular properties. *Water Research*,
396 45, 2439-2451.

397 [30] Verlicchi, P., Zambello, E. 2015. Pharmaceuticals and personal care products in
398 untreated and treated sewage sludge: Occurrence and environmental risk in the case of
399 application on soil — A critical review. *Science of The Total Environment*, 538, 750-
400 767.

401 [31] Wang, L., Wijekoon, K.C., Nghiem, L.D., Khan, S.J. 2014. Removal of polycyclic
402 musks by anaerobic membrane bioreactor: biodegradation, biosorption, and
403 enantioselectivity. *Chemosphere*, 117, 722-729.

- 404 [32] Wijekoon, C.K., Hai, I.F., Kang, J., Price, E.W., Wenshan Guo, Ngo, H.H., Cath, Y.T.,
405 Nghiem, D.L. 2014. A novel membrane distillation–thermophilic bioreactor system:
406 Biological stability and trace organic compound removal. *Bioresource Technology*,
407 159, 334-341.
- 408 [33] Wijekoon, K.C., McDonald, J.A., Khan, S.J., Hai, F.I., Price, W.E., Nghiem, L.D. 2015.
409 Development of a predictive framework to assess the removal of trace organic
410 chemicals by anaerobic membrane bioreactor. *Bioresource Technology*, 189, 391-398.

411 **List of Tables**

412 **Table 1:** Biological performance of the three digesters (average $\pm$ standard deviation of at
413 least eight separate samples).

Parameters	Digester SRT (d)		
	15	20	30
TS reduction (%)	59.3 $\pm$ 15.0	63.3 $\pm$ 14.7	68.6 $\pm$ 11.7
VS reduction (%)	69.3 $\pm$ 11.8	73.5 $\pm$ 12.0	75.8 $\pm$ 8.8
tCOD removal (%)	70.2 $\pm$ 5.6	71.9 $\pm$ 7.8	77.1 $\pm$ 5.3
sCOD removal (%)	49.5 $\pm$ 18.6	45.8 $\pm$ 15.3	53.4 $\pm$ 12.1

414

Table 2: Occurrence of TrOCs of primary sludge in aqueous phase and solid phase (average $\pm$ standard deviation of samples taken every 10 days over 12 weeks).

Compounds	Log D at pH 5	Concentration		Mass distribution	
		Aqueous phase (ng/L)	Solid phase (ng/kg dry sludge)	Aqueous phase (%)	Solid phase (%)
Atenolol	-2.75	2,649 $\pm$ 1,310	94,000 $\pm$ 93,000	52	48
Trimethoprim	-1.33	1,095 $\pm$ 263	98,000 $\pm$ 67,000	29	71
Caffeine	-0.63	50,910 $\pm$ 19,501	910,000 $\pm$ 497,000	64	36
Paracetamol	0.48	64,104 $\pm$ 52,814	898,000 $\pm$ 843,000	71	29
Primidone	0.83	184 $\pm$ 142	22,000 $\pm$ 25,000	23	77
Fluoxetine	0.83	192 $\pm$ 102	61,000 $\pm$ 31,000	10	90
Clozapine	0.96	324 $\pm$ 97	1,699,000 $\pm$ 4,270,000	1	99
Verapamil	0.98	117 $\pm$ 38	132,000 $\pm$ 69,000	3	97
Amitriptyline	1.35	791 $\pm$ 328	1,023,000 $\pm$ 2,398,000	3	97
Carbamazepine	1.89	5,271 $\pm$ 1,676	154,000 $\pm$ 88,000	56	44
Naproxen	2.49	2,809 $\pm$ 656	23,000 $\pm$ 23,000	82	18
Diuron	2.68	220 $\pm$ 47	21,000 $\pm$ 12,000	27	73
Ibuprofen	2.81	12,503 $\pm$ 4,716	721,000 $\pm$ 1,139,000	40	60
Bisphenol A	3.64	1,700 $\pm$ 1,210	163,000 $\pm$ 86,000	27	73
Diclofenac	3.66	419 $\pm$ 217	19,000 $\pm$ 16,000	43	57
Gemfibrozil	3.86	250 $\pm$ 124	24,000 $\pm$ 13,000	28	72
Triclosan	5.34	10,680 $\pm$ 4,506	1,965,000 $\pm$ 1,171,000	16	84
Triclocarban	6.07	9,212 $\pm$ 5,515	4,308,000 $\pm$ 1,836,000	7	93

418 **List of Figure Captions**

419 **Figure 1:** Methane production activities and biogas composition at SRT of 15, 20, and 30
420 days.

421 **Figure 2:** Concentration of TrOCs of primary sludge and digested sludge in aqueous phase
422 (error bars show the standard deviation of 12 independent samples).

423 **Figure 3:** Concentration of TrOCs of primary sludge and digested sludge in solid phase (error
424 bars show the standard deviation of 12 independent samples).

425 **Figure 4:** Mass distribution of TrOCs after anaerobic digestion at SRT of (a) 15, (b) 20, and
426 (c) 30 days.

428

429 **Figure 1**

Figure 2

Figure 3

Figure 4

Occurrence of trace organic contaminants in wastewater sludge and their removals by anaerobic digestion

SUPPLEMENTARY INFORMATION

Submitted to Bioresource Technology

Shufan Yang ^a, James McDonald ^c, Faisal I. Hai ^a, William E. Price ^b, Stuart J. Khan ^c,
Long D. Nghiem ^{a*}

^a Strategic Water Infrastructure Lab, School of Civil, Mining and Environmental Engineering, University of Wollongong, Australia

^b Strategic Water Infrastructure Lab, School of Chemistry, University of Wollongong Australia

^c School of Civil and Environmental Engineering, University of New South Wales, NSW 2052, Australia

* Corresponding author: longn@uow.edu.au; Ph: +61 (2) 4221 4590.

Figure S1: Schematic diagram of the anaerobic digester.

Table S2: List compounds being monitored (isotopically labelled standards were added to the primary sludge) in this study.

No.	Compounds	Detected in primary sludge
1	Tris(2-carboxyethyl)phosphine	No
2	Atenolol	Yes
3	Caffeine	Yes
4	Sulfamethoxazole	No
5	Enalapril	No
6	Ketoprofen	No
7	Trimethoprim	Yes
8	Paracetamol	Yes
9	Meprobamate	No
10	Naproxen	Yes
11	Primidone	Yes
12	Ibuprofen	Yes
13	Triamterene	No
14	Fluoxetine	Yes
15	Dilantin (phenytoin)	No
16	Risperidone	No
17	Diclofenac	Yes
18	Carbamazepine	Yes
19	Gemfibrozil	Yes
20	Verapamil	Yes
21	Hydroxyzine	No
22	Amitriptyline	Yes
23	Simazine	No
24	Omeprazole	No
25	Atrazine	Yes
26	Diuron	Yes
27	Diazepam	No
28	Linuron	No
29	Clozapine	Yes
30	Phenylphenol	No
31	Bisphenol A	Yes
32	Diazinon	No
33	Triclosan	Yes
34	Triclocarban	Yes
35	4-n-nonylphenol	No
36	Polyparaben (polymer)	No

Figure S3: Alkalinity of digested sludge at three different sludge retention time of 15, 20, and 30 days.

Table S4: Molecular structure of the 18 TrOCs detected in the primary sludge this study.

Compounds	Structure	Compounds	Structure
Atenolol		Carbamazepine
Caffeine		Gemfibrozil
Trimethoprim		Verapamil
Paracetamol		Amitriptyline
Naproxen		Diuron
Primidone		Clozapine
Ibuprofen		Bisphenol A
Fluoxetine		Triclosan
Diclofenac		Triclocarban

Table S5: Examples of electron donating and withdrawing functional groups.

Strong electron donating functional groups	Strong electron withdrawing functional groups
$\begin{array}{c} \text{R} \\ \diagup \\ \text{---N} \\ \diagdown \\ \text{R} \end{array}$ ---NH---C(=O)---R ---C(=O)NH--- ---O---R ---OH ---NHR	$\begin{array}{c} \text{O} \\ \parallel \\ \text{---C---NH}_2 \end{array}$ $\begin{array}{c} \text{O} \\ \parallel \\ \text{---C---OH} \end{array}$ $\begin{array}{c} \text{F} \\ \\ \text{---C---F} \\ \\ \text{F} \end{array}$ $\begin{array}{c} \text{O} \\ \parallel \\ \text{---CH} \end{array}$

RESEARCH HIGHLIGHTS

- 18 TrOCs were consistently detected in raw primary sludge
- These TrOCs occurred predominantly in the solid phase
- TrOC removal by anaerobic digestion was governed by their molecular structure
- An increase in SRT value led to an increase in biogas production and VS removal
- However, SRT increase did not lead to any discernible increase in TrOC removal