



UNIVERSITY
OF WOLLONGONG
AUSTRALIA

University of Wollongong
Research Online

University of Wollongong Thesis Collection
1954-2016

University of Wollongong Thesis Collections

2004

Synthesis, characterisation and applications of conducting polymer coated textiles

Jian Wu

University of Wollongong

UNIVERSITY OF WOLLONGONG

COPYRIGHT WARNING

You may print or download ONE copy of this document for the purpose of your own research or study. The University does not authorise you to copy, communicate or otherwise make available electronically to any other person any copyright material contained on this site. You are reminded of the following:

This work is copyright. Apart from any use permitted under the Copyright Act 1968, no part of this work may be reproduced by any process, nor may any other exclusive right be exercised, without the permission of the author.

Copyright owners are entitled to take legal action against persons who infringe their copyright. A reproduction of material that is protected by copyright may be a copyright infringement. A court may impose penalties and award damages in relation to offences and infringements relating to copyright material. Higher penalties may apply, and higher damages may be awarded, for offences and infringements involving the conversion of material into digital or electronic form.

Recommended Citation

Wu, Jian, Synthesis, characterisation and applications of conducting polymer coated textiles, Doctor of Philosophy thesis, Department of Chemistry - Faculty of Science, University of Wollongong, 2004. <http://ro.uow.edu.au/theses/1191>

Research Online is the open access institutional repository for the University of Wollongong. For further information contact the UOW Library: research-pubs@uow.edu.au

NOTE

This online version of the thesis may have different page formatting and pagination from the paper copy held in the University of Wollongong Library.

UNIVERSITY OF WOLLONGONG

COPYRIGHT WARNING

You may print or download ONE copy of this document for the purpose of your own research or study. The University does not authorise you to copy, communicate or otherwise make available electronically to any other person any copyright material contained on this site. You are reminded of the following:

Copyright owners are entitled to take legal action against persons who infringe their copyright. A reproduction of material that is protected by copyright may be a copyright infringement. A court may impose penalties and award damages in relation to offences and infringements relating to copyright material. Higher penalties may apply, and higher damages may be awarded, for offences and infringements involving the conversion of material into digital or electronic form.

**SYNTHESIS, CHARACTERISATION AND
APPLICATIONS OF CONDUCTING POLYMER
COATED TEXTILES**

**A thesis submitted in fulfillment of the requirements
for the award of the degree**

DOCTOR OF PHILOSOPHY

from

UNIVERSITY OF WOLLONGONG

by

JIAN WU, B.Sc.

Department of Chemistry

May 2004

*To my parents for their encouragement,
especially in memory of my father*

*To my husband Xifa Yang and my daughter Wenxin Yang
for their support and patience*

THESIS CERTIFICATION

I, Jian WU, declare that this thesis, submitted in fulfillment of the requirements for the award of Doctor of Philosophy, in the Department of Chemistry, University of Wollongong, is wholly my own work unless otherwise referenced or acknowledged. The document has not been submitted for qualifications at any other academic institution.

Jian WU

May 2004

ACKNOWLEDGEMENTS

I wish to express my sincere gratitude to my supervisors Professor Gordon G. Wallace and Dr. Dezhi Zhou for their enthusiastic supervision and encouragement through this work.

I also deeply appreciate helpful assistance of the staff and students at the Intelligent Polymer Research Institute, especially Professor Leon Kane-Maguire, Associate Professor Geoff Spinks, Dr. Chee Too, Dr. Peter Innis, Dr. Toni Campbell, Dr. Syed Ashraf, Dr. Jie Ding, Dr. Jun Chen, Dr. Simon Moulton, Dr. Norman Barisci and Dr. Benny Kim. Also, I would like to thank Dr. Violeta Misoska and Dr. Jiazhao Wang for their help in running samples on the SEM. Thanks also to Miss Jenny Causley and Dr. K. Konstantinov for their help on HPLC and TGA analysis. I would like to address the help and support of Binbin Xi, Yanzhe Wu, Chunming Yang and Phil Smugreski. I would like to acknowledge the technical assistances of S. Butler and P. Sarakinotis.

I am grateful to the Intelligent Polymer Research Institute and CSIRO for the award of a postgraduate scholarship. Finally, I would like to acknowledge Dr. Mark Loony and Peter Waters from CSIRO TFT for their technical advice and assistance.

PUBLICATIONS

- 1 J. Wu, D. Zhou, C. Too and G. G. Wallace, “Conducting Polymers Coated Textile” ICSM 2004 and *Synthetic Metals* (Submitted).
- 2 “Electromechanical actuators based on fibre and fabrics” G. G. Wallace, J. Wu, V. Aboutanos, G. M. Spinks and D. Zhou, SPIE (2001) [4329-55].
- 3 G.G. Wallace, G. M. Spinks, J. Wu and D. Zhou, “Electrofunctional materials: strain gauges and actuators in fabric structures (Invited paper), SPIE, Smart Materials and MEMS (2000) [4234-4235].

ABSTRACT

This thesis describes preparation and characterisation of a range of novel conducting polymer coated textiles, which have potential in applications such as static dissipation, EMI shielding, heating elements, composite structures and many military applications.

Conducting polypyrrole coated textiles such as nylon Lycra and polyester fabrics have been synthesised using different approaches (Chapter 3). The present study concentrates on preparation of conducting polypyrrole coated textile using an *in-situ* polymerisation method. A range of characterisation techniques for the inherently conducting polymer (ICP) coated fabrics were used: the stability of the surface resistivity, cyclic voltammetry, Scanning Electron Microscopy (SEM), UV-Vis spectroscopy and Thermogravimetric analysis (TGA). It was found that the PPy-coated nylon Lycra fabric could be used as a wearable strain gauge. The strain gauge characteristics have been investigated using both an Instron machine and a “SmartMotor”.

The use of molecular templates to facilitate the polymerisation and the integration of inherently conducting polymers (ICPs) into textiles has been investigated (Chapter 4). Poly(2-methoxyaniline-5 sulfonic acid) or [PMAS] is a water-soluble, fully sulfonated polyaniline that has been used as molecular template. In the first step – “dyeing” of PMAS into the textile, the effect of fabric pre-treatment, solution pH as well as solution temperature have been investigated. In the second step the effects of the ratio of PMAS to aniline, the ratio of aniline to ammonium persulfate and the polymerisation temperature on the polymerisation reaction have also been studied. Characterisation of the templated polyaniline coated fabric prepared using the above “Two step” process

has been undertaken (Chapter 4). The stability of the conductivity, cyclic voltammetry, UV-Vis spectra, SEM studies, TGA analysis and strain gauge characteristics have been determined. Results indicate that templated PAN-coated wool nylon Lycra can be used as the strain gauge as tested with either the Instron machine or “SmartMotor”.

Conducting polymer coated textile fabrics are easily prepared and integrated into truly wearable clothing and garments to create strain sensors with a wide dynamic range. Functional wearable textile sensing systems can monitor human motion, provide immediate bio-feedback to the wearer without changing the properties and functions of the fabric material and with no interference to normal human body motion. This innovative technique can be widely used for injury prevention, rehabilitation, sport technique modification and medical treatment. It will have a number of further potential applications to be used for daily living, work and recreation in the future.

ABBREVIATIONS

μ	micro
$^{\circ}\text{C}$	degree Celsius
A^{-}	anion
ABS	absorbance
Ag/AgCl	silver/silver chloride reference electrode
CEP	conducting electroactive polymer
cm	centimeter
CV	cyclic voltammetry
ΔE	potential difference
E	potential
$\text{E}_{\text{p(a)}}$	anodic peak potential
$\text{E}_{\text{p(c)}}$	cathodic peak potential
EB	emeraldine base
ES	emeraldine salt
g	gram
HPLC	high performance liquid chromatography
I	current
ITO	Indium-tin oxide
K	Kelvin
LB	leucoemeraldine base
M	molar
mA	milliampere(s)
mV	millivolt

n	number of electron
NDSA	1,5-naphthalenedisulfonic acid tetrahydrate
PAn	polyaniline
PB	pernigraniline base
PMAS	poly(2-methoxyaniline-5-sulfonic acid)
PPy	polypyrrole
PS	pernigraniline salt
Pt	platinum
R	resistance
RVC	reticulated vitreous carbon
sec	second
SPAN	sulfonated polyaniline
SEM	scanning electron microscopy
TGA	Thermogravimetry analysis
UV-Vis	ultraviolet-visible

LIST OF FIGURES AND TABLES

1. Figures

Figure 1.1. Schematic of conducting polymers

Figure 1.2. Polypyrrole polymerisation initiation and polymer growth

Figure 1.3. Interconversions between different forms of polyaniline

Figure 1.4. Chemical polymerisation of aniline

Figure 1.5. Structures of some fully sulfonated polyanilines

Figure 1.6. Assignment of electronic absorption bands of emeraldine salt

Figure 1.7. UV-Vis spectra of (a) initial emeraldine salt PAn.(+)-HCSA film and (b) leucoemeraldine base film derived by reduction with PhNHNH₂

Figure 1.8. UV-Vis spectra of (a) initial emeraldine salt PAn.(+)-HCSA film and (b) pernigraniline base film derived by oxidation with ceric ammonium sulfate [93].

Figure 1.9. UV-Vis spectra of PMAS solution during oxidation in 0.1 M (NH₂)S₂O₈, pH 1

Figure 1.10. UV-Vis spectra of PMAS solution during reduction in 0.08 M hydrazine, pH 9

Figure 1.11. Classification of fibres

Figure 1.12. The morphological diagram of a wool fibre

Figure 1.13. The general formula of amino acid

Figure 1.14. Poly (ethylene terephthalate) polymerisation

Figure 1.15. Polymerisation steps used to produce Nylon 66 and Nylon 6 fibres

Figure 1.16. Photomicrograph of Lycra Spandex fibre in a cross-section

Figure 1.17. Photomicrograph of Lycra Spandex fibre in a longitudinal view

Figure 1.18. The repeat unit of a polyether based Spandex used in Lycra fabric

Figure 1.19. (a) The unstretched or amorphous state of the polymer system of an elastomeric fibre; (b) The stretched or more crystalline state of the polymer system of an elastomeric fibre

Figure 1.20. Woven fabrics: plain weave

Figure 1.21. 1/1 rib weft knitted fabric

Figure 1.22. Simple warp knit

Figure 1.23. Face side of the locknit fabric

Figure 1.24. Surface resistivity of various textile products

Figure 2.1. *In-situ* (chemical oxidation) polymerisation method used to coat fabrics

Figure 2.2. (a) Dyeing process of fabric (b) Top view of the fabric secured onto the spindle

Figure 2.3. Template polymerisation of conducting polyaniline on the PMAS-treated fabric.

Figure 2.4. Vapour-phase polymerisation method

Figure 2.5. Cyclic voltammetry cell for conducting polymer coated fabric

Figure 2.6. Cyclic voltammogram of PPy/NDSA coated nylon Lycra in 1.0 M NaNO₃ at a scan rate of 100 mVs⁻¹

Figure 2.7. Top view of the ASTM four-point probe method for the measurement of the electrical conductivity of a piece of conductive fabric. The distance between the two inner electrodes is 0.2 cm. The sample is sandwiched with another connector. A constant current is applied between the two outer electrodes

Figure 2.8. Top view of the AATCC-76 two-point probe method for the measurement of the electrical conductivity of a piece of conductive fabric. The distance between the two parallel electrodes is 1.5 cm. The sample is measured with a standard ohmmeter

Figure 2.9. UV-Visible spectra of PMAS solution before and after dyeing the wool nylon Lycra fabric

Figure 2.10. SEM image of a polypyrrole-NDSA coated nylon Lycra

Figure 2.11. Wheatstone bridge electrical resistance vs. strain testing circuit

Figure 2.12. Resistance vs Strain of polypyrrole coated nylon Lycra fabric when stretched to 50%

Figure 2.13. Force vs Strain of polypyrrole coated nylon Lycra fabric when stretched to 50%

Figure 2.14. Dynamic calibration apparatus

Figure 3.1. Both sides of PPy-coated nylon Lycra prepared at a current density of 2.0 mAcm^{-2} for 4 hours using electrochemical polymerisation

Figure 3.2. SEM of PPy-coated nylon Lycra prepared at a current density of 2.0 mAcm^{-2} for 4 hours using electrochemical polymerisation

Figure 3.3. SEM of PPy-coated nylon Lycra using the vapour polymerisation

Figure 3.4. Typical strain-resistance responses of PPy-coated nylon Lycra fabric under different cycles when stretched to 50%

Figure 3.5. PPy-coated Taffeta polyester after different polymerisation times

Figure 3.6. Resistance change of PPy-coated polyester versus strain

Figure 3.7. The surface resistivity (Ω/\square) of PPy-coated nylon Lycra at different areas of the A4 fabric

Figure 3.8. The surface resistivity (Ω/\square) of PPy-coated nylon Lycra at different areas of coated fabric (7.4 cm x 10.5 cm).

Figure 3.9. The changes of surface resistivity vs storage time of PPy-coated nylon Lycra. Broken line: stored in the open air, bold line: stored in a desiccator

Figure 3.10. Cyclic voltammogram of PPy/NDSA film (ca. 0.1 μm thickness) in 1.0 M NaNO_3 at a scan rate of 100 mV s^{-1}

Figure 3.11. Cyclic voltammogram of PPy/NDSA coated nylon Lycra in 1.0 M NaNO_3 at a scan rate of 100 mVs^{-1}

Figure 3.12. Scanning electron micrograph of uncoated nylon Lycra fibre

Figure 3.13. Scanning electron micrograph of PPy-coated nylon Lycra fibre

Figure 3.14. UV-Vis spectra of uncoated and PPy-coated nylon Lycra fabrics

Figure 3.15. TGA (60-600 $^\circ\text{C}$) of PPy/NDSA powder under nitrogen gas

Figure 3.16. TGA (60-600 $^\circ\text{C}$) of dopant NDSA under nitrogen gas

Figure 3.17. TGA (50-500 $^\circ\text{C}$) of uncoated and PPy-coated nylon Lycra fabrics under nitrogen gas

Figure 4.1. Branched structures of the traditional ortho-para directed enzymatic polymerisation of aniline that results in an electrically inactive form of aniline vs enzymatic polymerization in the presence of SPS

Figure 4.2. Poly (2-methoxyaniline-5 sulfonic acid) (PMAS) structure

Figure 4.3. Thermobath with temperature control used in the dyeing process

Figure 4.4. The spindle with wool fabric before (a) and after (b) dyeing with PMAS

Figure 4.5. Beer's Law plot for aqueous PMAS solution

Figure 4.6. Surface resistivity vs. storage time for PMAS-treated wool nylon Lycra

Broken line: stored in the open air, bold line: stored in a sealed plastic bag.

Figure 4.7. Changes in surface resistivity vs. time for wool nylon Lycra coated with PMAS then coated with PAn prepared at room temperature. Broken line: stored in the open air, bold line: stored in a sealed plastic bag.

Figure 4.8. Changes in surface resistivity vs. time. PMAS templated polyaniline wool nylon Lycra prepared at lower temperature (2-3 °C). Broken line: stored in the open air, bold line: stored in a sealed plastic bag.

Figure 4.9. Cyclic voltammogram of polyaniline (HCl) on a glassy carbon electrode in 1 M HCl at a scan rate of 50 mV/s

Figure 4.10. Cyclic voltammogram (CV) obtained using PMAS-treated wool nylon Lycra as the working electrode in 1 M HCl at a scan rate of 10 mV/s

Figure 4.11. Cyclic voltammogram (CV) obtained using PMAS templated polyaniline coated wool nylon Lycra as working electrode in 1 M HCl at a scan rate of 10 mV/s

Figure 4.12. Cyclic voltammograms (CV) obtained using PMAS templated polyaniline coated wool nylon Lycra as working electrode in 1 M HCl at a scan rate of 10 mV/s. Pink line: stored in the open air for 55 days, blue line: stored in a sealed plastic bag for 55 days.

Figure 4.13. UV-Visible spectra of uncoated, PMAS & *in-situ* templating coated wool nylon Lycra using *ortho*-dichlorobenzene as a solvent

Figure 4.14. UV-Visible spectra of PMAS templated PAN coated wool nylon Lycra under different storage conditions for 55 days

Figure 4.15. UV-Visible spectra of oxidised / reduced forms of PMAS templated PAN-coated wool nylon Lycra

Figure 4.16. UV-Visible spectra of coated wool nylon Lycra before and after heating at 100 °C and 210 °C for 2 hours

Figure 4.17. Scanning electron micrograph of uncoated wool nylon Lycra fibre.

Figure 4.18. Scanning electron micrograph of PMAS-treated wool nylon Lycra fibre.

Figure 4.19. Scanning electron micrograph PMAS templated PAN-coated wool nylon

Figure 4.20. TGA (60-500 °C) PMAS powder

Figure 4.21. TGA (60-600 °C) of templated PAn powder (PMAS+PAn copolymer)

Figure 4.22. TGA (60-600 °C) of uncoated, PMAS-treated and templated PAn coated wool nylon Lycra fabrics

Figure. 5.1. Stress-strain responses of uncoated nylon Lycra fabric for the first two cycles when stretched to 50%

Figure 5.2. Stress-strain responses of uncoated nylon Lycra fabric for the fifth and the sixth cycles when stretched to 50%

Figure 5.3. Stress-strain responses of PPy-coated nylon Lycra fabric for the first two cycles when stretched to 50%

Figure 5.4. Stress-strain responses of PPy-coated nylon Lycra fabric for the fifth and the sixth cycles when stretched to 50%

Figure 5.5. Stress-strain of uncoated and PPy-coated nylon Lycra fabrics in the wale direction at different strains

Figure 5.6. Stress-strain responses of uncoated wool nylon Lycra fabric for the first two cycles when stretched to 50%

Figure 5.7. Stress-strain responses of uncoated wool nylon Lycra fabric for the fifth and the sixth cycles when stretched to 50%

Figure 5.8. Stress-strain responses of PMAS-treated wool nylon Lycra fabric for the first two cycles when stretched to 50%

Figure 5.9. Stress-strain responses of PMAS-treated wool nylon Lycra fabric for the fifth and the sixth cycles when stretched to 50%

Figure 5.10. Stress-strain responses of PMAS templated PAn-coated wool nylon Lycra fabric for the first two cycles when stretched to 50%

Figure 5.11. Stress-strain responses of PMAS templated PAn-coated wool nylon Lycra fabric for the fifth and the sixth cycles when stretched to 50%

Figure 5.12. Stress-strain of uncoated, PMAS-treated and PMAS templated PAn-coated wool nylon Lycra fabrics in the wale direction at different strains

Figure 5.13. Resistance/Strain relationship for nylon Lycra in the wale and course direction

Figure 5.14. Resistance-strain of PPy-coated nylon Lycra fabric for the first two cycles when stretched to 50%

Figure 5.15. Resistance-strain of PPy-coated nylon Lycra fabric for the fifth and the sixth cycles when stretched to 50%

Figure 5.16. Resistance-strain on PPy-coated nylon Lycra fabric in the wale direction at different strains

Figure 5.17. Resistance-strain of PMAS templated PAn-coated wool nylon Lycra fabric for the first two cycles when stretched to 50%

Figure 5.18. Resistance-strain responses of PMAS templated PAn-coated wool nylon Lycra fabric for the fifth and the sixth cycles when stretched to 50%

Figure 5.19. Resistance-strain responses for PMAS templated PAn-coated wool nylon Lycra 7010 fabric in the wale direction at different strain

Figure 5.20. Ratio of change in resistance to initial resistance ($\Delta R/R_i$) of PPy-coated nylon Lycra when stretched to 50%

Figure 5.21. Ratio of change in resistance to initial resistance ($\Delta R/R_i$) of PMAS templated PAn-coated wool nylon Lycra when stretched to 70%

Figure 5.22. Electronic signal of resistance response on PPy-coated nylon Lycra at 1 Hz when stretched to 50%

Figure 5.23. Changes in resistance of PPy-coated nylon Lycra fabric in the wale direction at 1 Hz under different strains

Figure 5.24. Changes in resistance of PPy-coated nylon Lycra fabric in the wale direction at different frequencies under different strains

Figure 5.25. Electronic signal of resistance responses on PMAS templated PAN-coated wool nylon Lycra at strain=50%

Figure 5.26. Changes of resistance on PMAS templated PAN-coated wool nylon Lycra fabric in the wale direction at different strain

Figure 5.27. Ratio of change in resistance to initial resistance ($\Delta R/R_i$) of PPy-coated nylon Lycra when stretched from 10% to 50%

Figure 5.28. Ratio of change in resistance to initial resistance ($\Delta R/R_i$) of PMAS templated PAN-coated wool nylon Lycra when stretched from 10% to 70%

Figure 6.1. The joint angle, ϕ , for the knee

Figure 6.2. “Intelligent Elbow Strain Gauge”

Figure 6.3. Changes in resistance of PPy-coated nylon Lycra strip on the “Intelligent Elbow Strain Gauge” under different strain ranges

Figure 6.4. Knee sleeve system

Figure 6.5. Intelligent Knee Sleeve

Figure 6.6. Football player wearing the “intelligent knee sleeve” and training to land correctly to protect his knee from potential ligament damage

Figure 6.7. The rehabilitation glove with PPy-coated fabric sensor strips on each finger

2. Tables

Table 1.1. Techniques used for characterisation of conducting polymers.

Table 3.1. Optimisation of molar concentrations of pyrrole/FeCl₃/NDSA

Table 3.2. Optimisation of molar concentrations of pyrrole/FeCl₃/NDSA

Table 3.3. Optimisation of molar concentrations of pyrrole/FeCl₃/NDSA

Table 3.4. Summary of electrochemical polymerisation for PPy-coated nylon Lycra at different current densities

Table 3.5. Summary of electrochemical polymerisation for PPy-coated nylon Lycra at different polymerisation times

Table 3.6. The surface resistivity of PPy-coated nylon Lycra using different concentrations of FeCl_3 in ethanol for soaking the fabric prior to monomer exposure

Table 3.7. The surface resistivity of PPy-coated nylon Lycra using different solvents for oxidant uptake into the textile

Table 3.8. The surface resistivity of PPy-coated nylon Lycra using different temperature for vapour generation

Table 3.9. The surface resistivity and strain gauge factors for PPy-coated nylon Lycra – effect of pyrrole monomer concentrations

Table 3.10. The surface resistivity and gauge factors of PPy-coated nylon Lycra produced under different oxidant FeCl_3 concentrations

Table 3.11. The surface resistivity and gauge factors of PPy-coated nylon Lycra obtained using different dopant concentrations

Table 3.12. The surface resistivity and gauge factor of PPy-coated nylon Lycra obtained by using different reaction times

Table 3.13. The surface resistivity and gauge factors of PPy-coated nylon Lycra produced at different polymerisation temperatures

Table 3.14. The surface resistivity of PPy-coated Taffeta polyester after different polymerisation times

Table 4.1. Summary of wool nylon Lycra washed with and without Sandoclean PC Liquid

Table 4.2. Effect of variation of pH on the application of PMAS

Table 4.3. The effect of variation of temperatures on the application of PMAS

Table 4.4. The surface resistivity of the PMAS templated PAn-coated wool nylon Lycra produced under different PMAS:Aniline ratios

Table 4.5. The surface resistivity of the PMAS templated PAn-coated wool nylon Lycra fabrics produced using different Aniline:APS ratios

Table 4.6. Surface resistivity of the PMAS templated PAn - coated wool nylon Lycra prepared using different temperatures for aniline oxidation

Table 4.7. Consumption of aniline monomer during polymerisation in the presence of PMAS templated wool nylon Lycra using different reaction temperatures

CONTENTS

DEDICATION	I
CERTIFICATION	II
ACKNOWLEDGMENTS	III
PUBLICATIONS	IV
ABSTRACT	V
ABBREVIATIONS	VII
LIST OF FIGURES AND TABLES	IX
CHAPTER 1	1
GENERAL INTRODUCTION	1
1.1 CONDUCTING POLYMERS	2
1.1.1. The Development of Conducting Polymer	2
1.1.2. Polypyrrole	3
1.1.3. Polyaniline	6
1.1.3.1. Unsubstituted Polyaniline (PAn)	7
1.1.3.2. Sulfonated Polyaniline	11
1.1.4. Characterisation of Conducting Polymers	15
1.2 FIBRE STRUCTURE & TEXTILE SUBSTRATE	16
1.2.1. Fibre Structure	18
1.2.1.1. Wool Fibre	18
1.2.1.2. Polyester Fibre	21
1.2.1.3. Nylon Fibre	24
1.2.1.4. Spandex Fibre – Lycra Fibre	26

1.2.2. Fabric Textile Structure	30
1.2.2.1. Woven Fabrics	31
1.2.2.2. Knitted Fabrics	33
1.3. ELECTRICALLY CONDUCTING TEXTILES	37
1.3.1. Carbon Fibres and Carbon-filled Materials	38
1.3.2. Metallic Fibres	38
1.3.3. Metal Coated Materials	39
1.3.4. Conducting Polymer Coated Textiles	40
1.3.4.1. Polypyrrole Coated Textiles	42
1.3.4.2. Polyaniline Coated Textiles	44
1.3.4.3. Properties of Conductive Textiles	45
1.4. AIMS OF THE PROJECT	46
1.5. REFERENCES	49
CHAPTER 2	59
GENERAL EXPERIMENTAL TECHNIQUES	59
2.1. INTRODUCTION	60
2.2. PREPARATION OF CONDUCTIVE POLYMER COATED TEXTILES	61
2.2.1. Chemical Polymerisation	61
2.2.1.1. <i>In-situ</i> Polymerisation (Chemical Oxidation) Process	61
2.2.1.2. Template Polymerisation Process	62
2.2.1.3. Chemical oxidation Using Vapour Phase Monomer	65
2.2.2. Electrochemical Polymerisation	66

2.3.	CHARACTERISATION METHODS FOR CONDUCTIVE POLYMER COATED TEXTILE	67
2.3.1.	Cyclic Voltammetry (CV)	67
2.3.2.	Electrical Conductivity	69
2.3.3.	UV-Vis Spectroscopy	72
2.3.4.	Scanning Electron Microscopy (SEM)	73
2.3.5.	Thermogravimetric Analysis	74
2.3.6.	High Performance Liquid Chromatography (HPLC)	75
2.3.7.	Instron Testing to Determine Stress/strain Curves	76
2.3.8.	Use of SmartMotor to Determine Strain Gauge Characteristics at Different Frequencies	79
2.4.	REFERENCES	81
	CHAPTER 3	82
	PREPARATION AND CHARACTERISATION OF POLYPYRROLE COATED FABRICS	82
3.1.	INTRODUCTION	83
3.2.	EXPERIMENTAL	85
3.2.1.	Reagents and Materials	85
3.2.2.	Instrumentation	86
3.2.3.	Preparation of PPy-coated Fabrics Using Different Techniques	86
3.2.3.1.	Electrochemical Polymerisation	86
3.2.3.2.	Chemical Oxidation Using Vapour-phase Monomer	87
3.2.3.3.	<i>In-situ</i> Chemical Oxidation	88
3.2.3.3.1.	Preparation of PPy-coated Nylon Lycra Fabric	89

3.2.3.3.2. Preparation of PPy-coated Polyester Taffeta Fabric	91
3.2.4. Characterisation of PPy-coated Nylon Lycra Fabric	91
3.2.4.1. Surface Resistivity	92
3.2.4.2. Cyclic Voltammetry	92
3.2.4.3. Morphology Analysis	92
3.2.4.4. UV-Vis Spectra	93
3.2.4.5. Thermogravimetric Analysis	93
3.2.4.6. Strain & Stress Testing by Instron 4302 Tensile Tester	93
3.3. RESULTS AND DISCUSSION	94
3.3.1. Effect of Reaction Conditions on Surface Resistivity of PPy-coated Nylon Lycra Coated Using Electrochemical Polymerisation	94
3.3.2. Effect of Reaction Conditions on Surface Resistivity of PPy-coated Nylon Lycra Coated Using Chemical Oxidation of Monomer from Vapour Phase	98
3.3.3. Effect of Reaction Conditions on Surface Resistivity and Gauge Factor of PPy-coated Nylon Lycra Coated Using Chemical Oxidation	101
3.3.3.1. Effect of Pyrrole Monomer Concentration	101
3.3.3.2. Effect of Oxidant Concentration	104
3.3.3.3. Effect of Dopant Concentration	105
3.3.3.4. Effect of Reaction Time	106
3.3.3.5. Effect of Reaction Temperature	108
3.3.4. Effect of Reaction Conditions on Surface Resistivity and Gauge Factor of PPy-coated Polyester Taffeta	109

3.3.5. Characterisation of PPy-coated Nylon Lycra Fabric	113
3.3.5.1. Uniformity of Coated Fabric	113
3.3.5.2. Stability (Surface Resistivity Change vs Time) of PPy-coated Fabric	115
3.3.5.3. Cyclic Voltammetry of PPy-coated Fabric	116
3.3.5.4. Morphology of PPy-coated Fabric	119
3.3.5.5. UV-Vis Spectra of PPy-coated Fabric	121
3.3.5.6. Thermogravimetric Analysis	122
3.4. CONCLUSION	125
3.5. REFERENCES	129
CHAPTER 4	131
PREPARATION AND CHARACTERISATION OF POLYANILINE COATED FABRICS	131
4.1. INTRODUCTION	132
4.2. EXPERIMENTAL	135
4.2.1. Reagents and Materials	135
4.2.2. Instrumentation	136
4.2.3. Preparation of PMAS Templated PAn-coated Fabric	137
4.2.3.1. Integration of the Molecular Template-PMAS (Step One)	137
4.2.3.2. Integration of Cationic Inherently Conducting Polymers (Step Two)	140
4.2.4. Characterisation of PMAS Templated PAn-coated Wool Fabric	141
4.2.4.1. Surface Resistivity	141
4.2.4.2. Cyclic Voltammetry	142

4.2.4.3.	UV-Vis Spectral Analysis	142
4.2.4.4.	SEM	142
4.2.4.5.	Thermogravimetric Analysis	143
4.3.	RESULTS AND DISCUSSION	143
4.3.1.	Effect of Reaction Conditions on Integration of the Molecular Template- PMAS	143
4.3.2.	Effect of Reaction Conditions on Coating of Templated Textile with Polyaniline	148
4.3.2.1.	Effect of Aniline to PMAS Ratio	148
4.3.2.2.	Effect of Oxidant Concentration	149
4.3.2.3.	Polymerisation Temperature	151
4.3.2.4.	Aniline Monomer Consumption at Different Temperatures	152
4.3.3.	Characterisation of PMAS Templated PAn-coated Fabrics	153
4.3.3.1.	Surface Resistivity Change vs Time of PMAS-treated Wool Fabrics	153
4.3.3.2.	Surface Resistivity Change vs Time of PMAS Templated PAn-coated Wool Fabrics	154
4.3.3.3.	Cyclic Voltammetry	156
4.3.3.4.	UV-Vis Spectra	160
4.3.3.5.	SEM	164
4.3.3.6.	Thermogravimetry	167
4.4.	CONCLUSION	171
4.5.	REFERENCES	174

CHAPTER 5	176
CONDUCTIVE POLYMER COATED TEXTILES AND THEIR STRAIN GAUGE CHARACTERISTICS	176
5.1. INTRODUCTION	177
5.2. EXPERIMENTAL	178
5.2.1. Materials	178
5.2.2. Instrumentation	179
5.3. RESULTS AND DISCUSSION	180
5.3.1. Mechanical Properties of Uncoated and Polymer-coated Fabrics by Instron 4320 Tensile Tester	180
5.3.1.1. PPy-coated Nylon Lycra	180
5.3.1.2. Templated PAn-coated Wool Nylon Lycra	185
5.3.2. Strain Gauge Response of Polymer-coated Fabrics	191
5.3.2.1. PPy-coated Nylon Lycra	192
5.3.2.2. Templated PAn-coated Wool Nylon Lycra	195
5.3.3. Strain Gauge Response of Polymer-coated Fabrics at Different Frequencies	200
5.3.3.1. PPy-coated Nylon Lycra	201
5.3.3.2. Templated PAn-coated Wool Nylon Lycra	204
5.4. CONCLUSION	208
5.5. REFERENCES	211
CHAPTER 6	212
APPLICATION OF CONDUCTING POLYMER COATED FABRICS	212
6.1. INTRODUCTION	213

6.2.	DEVELOPMENT OF STRETCHABLE CONDUCTIVE TEXTILES	217
6.2.1.	Strain Gauge Performance in Sport Training	217
6.2.2.	Conductive Stretchable Textiles for Sensors and Actuators	223
6.2.3.	Further Potential Applications	225
6.3.	CONCLUSIONS	226
6.4.	REFERENCES	228
 CHAPTER 7		230
GENERAL CONCLUSIONS		230